


LONGSHINE MICROSYSTEM, INC.
LCS-6624, LCS-6624G(REV. 1)

Q2/92

Data bus: 16-bit, ISA
 Size: half-length, full-height card
 Hard drives supported: Two IDE drives
 Floppy drives supported: Two 360KB, 720KB, 1.2MB, or 1.44MB
 Special Features: Two serial, one parallel
 LCS-6624-G: Game port



| CONNECTIONS | |
|--|----------|
| Function | Location |
| 34-pin data cable connector-floppy drive | J1 |
| 40-pin AT Interface (IDE) connector-internal | J2 |
| 16 pin game port-internal (LCS-6624-G) | J3 |
| 10-pin serial port 2-internal | J4 |
| DB-9 male connector-serial port 1 | J5 |
| DB-25 female connector-parallel port | J6 |
| 4-pin connector-drive active LED | JP1 |

Continued on next page . . .

LONGSHINE MICROSYSTEM, INC.
LCS-6624, LCS-6624G(REV. 1)

Continued on next page . . .

| USER CONFIGURABLE SETTINGS | | |
|-------------------------------------|--------------|-------------------|
| Function | Location | Setting |
| í Factory configured - do not alter | JP2/jumper 4 | closed |
| í Factory configured - do not alter | JP3/jumper 3 | closed |
| í Floppy drive enabled | JP4 | open |
| Floppy drive disabled | JP4 | closed |
| í Hard drive enabled | JP4A | open |
| Hard drive disabled | JP4A | closed |
| í Parallel port set to LPT2 on IRQ7 | JP5 & JP5A | pins 1 & 2 closed |
| Parallel port set to LPT3 on IRQ5 | JP5 & JP5A | pins 2 & 3 closed |
| í LCS-6624 not grounded to host | JP6 | open |
| LCS-6624 grounded to host | JP6 | closed |

| SERIAL PORT 1 (J5) CONFIGURATION | | | |
|---|--------|--------|--------|
| Port 2 | JP3/1 | JP2/2 | JP2/3 |
| í Serial port 1 set to COM1 (3F8H-3FFh) | closed | open | closed |
| Serial port 1 set to COM3 (3E8H-3EFh) | open | closed | closed |

| SERIAL PORT 2 (J4) CONFIGURATION | | | |
|---|--------|--------|--------|
| Port 2 | JP2/1 | JP2/2 | JP2/3 |
| í Serial port 2 set to COM2 (2F8H-2FFh) | closed | open | closed |
| Serial port 2 set to COM4 (2E8H-2EFh) | open | closed | closed |