Q3/94

LONGSHINE MICROSYSTEM, INC. LCS-6941

Data bus: 32-bit VESA

Floppy drives supported:

Size: Full-length, full-height card Four IDE (AT) Interface drives Four 360KB, 720KB, 1.2MB, 1.44MB drives Hard drive supported:

J3 JP1 JP2 BANK 1 JP3 BANK 0 C0557

CONNECTIONS		
Function	Location	
40-pin IDE(AT) interface connector	J1	
40-pin IDE(AT) interface connector	J2	
34-pin data cable connector - floppy drive	J3	
34-pin data cable connector - floppy drive	J4	
4-pin connector - drive active LED	JP1	

USER CONFIGURABLE SETTINGS			
Function	Location	Setting	
í Factory configured - do not alter	JP2	open	
í Floppy drive interface enabled	JP3	pins 1 & 2 closed	
Floppy drive interface disabled	JP3	pins 2 & 3 closed	

DRAM CONFIGURATION			
Size	Bank 0	Bank 1	
512KB	(2)256K x 9	NONE	
1MB	(2)256K x 9	(2)256K x 9	
2MB	(2)1M x 9	NONE	
4MB	(2)1M x 9	(2)1M x 9	
8MB	(2)4M x 9	NONE	
10MB	(2)4M x 9	(2)1M x 9	
16MB	(2)4M x 9	(2)4M x 9	