
Q LOGIC CORPORATION FAST!SCSI ISA

Data bus: 16-bit, ISA

Half-length, full-height card Up to seven SCSI devices Size: Hard drive supported: Floppy drives supported:

N/A



CONNECTIONS			
Function	Location		
50-pin SCSI connector - external	CN1		
50-pin SCSI connector - internal	CN2		
4-pin connector - Drive active LED	CN3		

Continued on next page . . .

Q2/95

Q LOGIC CORPORATION FAST!SCSI ISA

. . . continued from previous page

USER CONFIGURABLE SETTINGS				
Function	Location	Setting		
í I/O Address - 330h	JP3	pins 1 & 2 closed		
I/O Address - 230h	JP3	pins 2 & 3 closed		
í SCSI termination - enabled	JP8	open		
SCSI termination - disabled	JP8	closed		
Data transfer mode asynchronous	JP4/A	open		
Data transfer mode synchronous	JP4/A	closed		
í SCSI ID7	JP4/B	open		
SCSI ID6	JP4/B	closed		
í Parity - enabled	JP4/C	open		
Parity - disabled	JP4/C	closed		

BIOS SELEC	СТ	
Setting	JP6/A	JP6/B
í Enabled	closed	open
Disabled	open	open

BIOS ADDRESS SELECT					
Address	JP2/A	JP2/B			
í C8000	open	open			
CC000	open	closed			
D8000	closed	open			
DC000	closed	closed			

INTERRUPT SELECT						
IRQ	JP5/A	JP5/B	JP5/C	JP5/D	JP4/D	JP4/E
í IRQ11	open	closed	open	open	open	open
IRQ10	closed	open	open	open	closed	open
IRQ12	open	open	closed	open	closed	closed
IRQ15	open	open	open	closed	open	closed