
LONGSHINE MICROSYSTEM, INC. LCS-8634TBA (REV.A1)

NIC Type Transfer Rate Data Bus Topology Wiring Type Ethernet 10Mbps 16-bit ISA Star RG58A/U 50ohm coaxial AUI transceiver via DB-15 port Unshielded twisted pair Available

Boot ROM



BOOT ROM		
Setting	JP5	
í Disabled	Open	
Enabled	Closed	

COMPATABILITY MODE				
Setting JP4				
í Disabled	Open			
Enabled	Closed			
Note: If your system does not work with this card, set this option to enabled (closed).				

	CABLE TYPE	
Туре	JP2	JP89-F
Unshielded twisted pair	Closed	Optional
RG58A/U 50ohm coaxial	Open	Pins 1 & 2 closed
AUI transceiver via DB-15 port	Open	Pins 2 & 3 closed

Continued on next page . . .

LONGSHINE MICROSYSTEM, INC. LCS-8634TBA (REV.B1)

. . . continued from previous page

	INTERUPT REQUEST							
IRQ	JP1A	JP1B	JP1C	JP1D	JP1E	JP1F	JP1G	JP1H
í 3	Open	Open	Open	Open	Open	Open	Open	Closed
4	Open	Open	Open	Open	Open	Open	Closed	Open
5	Open	Open	Open	Open	Open	Closed	Open	Open
9	Open	Open	Open	Open	Closed	Open	Open	Open
10	Open	Open	Open	Closed	Open	Open	Open	Open
11	Open	Open	Closed	Open	Open	Open	Open	Open
12	Open	Closed	Open	Open	Open	Open	Open	Open
15	Closed	Open						

BASE MEMORY ADDRESS					
B; ₃e Address	JP7A	JP7B	JP7C	JP7D	JP7E
í C800h	Pins 1 & 2	Pins 1 & 2	Pins 2 & 3	Pins 1 & 2	Pins 1 & 2
CA00h	Pins 2 & 3	Pins 1 & 2	Pins 2 & 3	Pins 1 & 2	Pins 1 & 2
CC00h	Pins 1 & 2	Pins 2 & 3	Pins 2 & 3	Pins 1 & 2	Pins 1 & 2
CE00h	Pins 2 & 3	Pins 2 & 3	Pins 2 & 3	Pins 1 & 2	Pins 1 & 2
D000h	Pins 1 & 2	Pins 1 & 2	Pins 1 & 2	Pins 2 & 3	Pins 1 & 2
D200h	Pins 2 & 3	Pins 1 & 2	Pins 1 & 2	Pins 2 & 3	Pins 1 & 2
D400h	Pins 1 & 2	Pins 2 & 3	Pins 1 & 2	Pins 2 & 3	Pins 1 & 2
D600h	Pins 2 & 3	Pins 2 & 3	Pins 1 & 2	Pins 2 & 3	Pins 1 & 2
D800h	Pins 1 & 2	Pins 1 & 2	Pins 2 & 3	Pins 2 & 3	Pins 1 & 2
DA00h	Pins 2 & 3	Pins 1 & 2	Pins 2 & 3	Pins 2 & 3	Pins 1 & 2
DC00h	Pins 1 & 2	Pins 2 & 3	Pins 2 & 3	Pins 2 & 3	Pins 1 & 2
DE00h	Pins 2 & 3	Pins 2 & 3	Pins 2 & 3	Pins 2 & 3	Pins 1 & 2
Note: Pins designat	Note: Pins designated should be in the closed position.				

Continued on next page . . .

LONGSHINE MICROSYSTEM, INC. LCS-8634TBA (REV.B1)

. . . continued from previous page

I/O BASE ADDRESS				
/ Jdress	、'6A	、'6B	、 [,] 6C	
í 300h	Pins 1 & 2 closed	Pins 1 & 2 closed	Pins 1 & 2 closed	
320h	Pins 2 & 3 closed	Pins 1 & 2 closed	Pins 1 & 2 closed	
340h	Pins 1 & 2 closed	Pins 2 & 3 closed	Pins 1 & 2 closed	
360h	Pins 2 & 3 closed	Pins 2 & 3 closed	Pins 1 & 2 closed	
380h	Pins 1 & 2 closed	Pins 1 & 2 closed	Pins 2 & 3 closed	
3A0h	Pins 2 & 3 closed	Pins 1 & 2 closed	Pins 2 & 3 closed	
3C0h	Pins 1 & 2 closed	Pins 2 & 3 closed	Pins 2 & 3 closed	
3E0h	Pins 2 & 3 closed	Pins 2 & 3 closed	Pins 2 & 3 closed	

LINK INTEGRITY TEST				
Setting JP3				
í Enabled	Pins 2 & 3 closed			
Disabled	Pins 1 & 2 closed			