


# OCEAN INFORMATION SYSTEMS, INC.

## ETHERNET-2100 REV. 1.0

NIC Type: Ethernet  
 Transfer Rate: 10Mbps  
 Data Bus: 16-bit ISA  
 Topology: Linear Bus  
 Wiring Type: AUI transceiver via DB-15 port  
 RG58A/U 50ohm coaxial  
 Available  
 Boot ROM Available



WAIT STATE	
Setting	W1
0 wait state	Open
1 wait state	Closed

CABLE TYPE	
Type	W2-W9
RG-58A/U 50ohm coaxial	Pins 2 & 3 closed
AUI transceiver via DB-15 port	Pins 1 & 2 closed

DMA CHANNEL									
Channel	W10	W11	W12	W13	W14	W15	W16	W17	
DMA 5	Open	Closed	Open	Open	Open	Closed	Open	Open	
DMA 3	Closed	Open	Open	Open	Closed	Open	Open	Open	
DMA 6	Open	Open	Closed	Open	Open	Open	Closed	Open	
DMA 7	Open	Open	Open	Closed	Open	Open	Open	Closed	

Continued on next page . . .

OCEAN INFORMATION SYSTEMS, INC.  
 ETHERNET-2100 REV. 1.0

... continued from previous page

BOOT ROM	
Setting	W18
í Disablec	Open
Enablec	Closed

I/O ADDRESS AND BOOT ROM ADDRESS			
I/O Address	Boot ROM Address	W19	W20
í 300h	C8000h	Closed	Closed
320h	CC000h	Closed	Open
340h	D0000h	Open	Closed
360h	D4000h	Open	Open

INTERRUPT REQUEST				
IRQ	W21	W22	W23	W24
í IRQ3	Open	Closed	Open	Open
IRQ4	Open	Open	Closed	Open
IRQ5	Open	Open	Open	Closed
IRQ9	Closed	Open	Open	Open