
MATROX GRAPHICS, INC. I L L U M I N A T O R - P R O

CategoryVideoVideo Types SupportedXVGAVideo ProcessorUnidentifiedHighest Resolution SupportedUnidentifiedData Bus Type16-bit ISAMemory TypeDRAMMaximum Onboard Memory1MB



CONNECTIONS			
Purpose	Location	Purpose	Location
VGA feature connector	CN1	Video out	CN3
Video in	CN2		

SIGNAL ON HSYNC LINE		
Setting SW1/1		
Hsync	Off	
Csync	On	

VGA CLOCK		
Setting SW1/2		
Normal	On	
Inverted	Off	

MONITOR TYPE				
Setting SW2/2 SW2/3				
S-video	On	On		
Composite Off Off				
Note: SW2/2 is Chroma, SW2/3 is Luma.				

Continued next page...

MATROX GRAPHICS, INC. I L L U M I N A T O R - P R O

... continued from previous page.

LUMA OUT		
Setting	SW2/3	
Enable	On	
Disable	Off	

BLACK BURST		
Setting SW2/1		
75Ω	On	
Hi-Z	Off	

I/O BASE ADDRESS SELECTION			
Address	SW1/3	SW1/4	SW1/5
í C8000h	On	Off	On
C0000h	On	On	On
C4000h	Off	On	On
CC000h	Off	Off	On
D0000h	On	On	Off
D4000h	Off	On	Off
D8000h	On	Off	Off
DC000h	Off	Off	Off