


MIRO COMPUTER PRODUCTS, INC.
MIROCRYSTAL 10SD/VL

Category Video
Video Types Supported XVGA
Video Processor S3
Highest Resolution Supported 1280 x 1024
Data Bus Type 32-bit VESA Local Bus
Memory Type DRAM
Maximum Onboard Memory 2MB



CONNECTIONS			
Port	Location	Port	Location
15-pin analog video port	CN1	VESA feature connector	CN2

MONITOR TYPE SELECTION				
Type	SW1/1	SW1/2	SW1/3	SW1/4
35KHz Multi-frequency	On	On	On	Off
48KHz Multi-frequency	Off	Off	On	Off
58KHz Multi-frequency	On	Off	Off	Off
64-85KHz Multi-frequency	Off	Off	Off	Off

VESA CLOCK SPEED SELECTION	
Speed	JP1
≤33MHz	Pins 2 & 3 closed
>33MHz	Pins 1 & 2 closed

Continued next page...

MIRO COMPUTER PRODUCTS, INC.
MIROCRYSTAL 10SD/VL

... continued from previous page.

FACTORY CONFIGURED - DO NOT ALTER	
Jumper	Position
JP2	Pins 2 & 3 closed

DRAM CONFIGURATION		
Size	Bank 0	Bank 1
1MB	(2) 1024K x 4	NONE
2MB	(2) 1024K x 4	(8) 256K x 4