
## SUNIX CO., LTD. SUN-6334/1 (EX-4002)

Card Type Parallel card
Chip Set ST-78C34
Maximum Onboard Memory I/O Options Parallel port
Data Bus 16-bit ISA
Floppy drives supported None



CONNECTIONS					
Function	Location				
25-pin parallel port 1	P1				

USER CONFIGURABLE SETTINGS						
Setting	Label	Position				
í Factory configured - do not alter	JP3	5 & 6 closed				
í Factory configured - do not alter	JP4	5 & 6 closed				
Note: JP3 & JP4 are set for the DMA selection but are not used in this card.						

PARALLEL PORT 1 ADDRESS SELECTION								
LPT	JP1/1	JP1/2	JP1/3	JP1/4	JP1/5	JP1/6		
í LPT1(3BCh)	Closed	Open	Open	Open	Open	Open		
LPT2(378h)	Open	Closed	Open	Open	Open	Open		
LPT3(278h)	Open	Open	Closed	Open	Open	Open		
LPT4(268h)	Open	Open	Open	Closed	Open	Open		
LPT5(27Ch)	Open	Open	Open	Open	Closed	Open		
LPT6(26Ch)	Open	Open	Open	Open	Open	Closed		

PARALLEL PORT 1 INTERRUPT SELECTION									
IRQ	JP2/A	JP2/B	JP2/C	JP2/D	JP2/E	JP2/F	JP2/G	JP2/H	JP2/I
IRQ3	Closed	Open							
IRQ4	Open	Closed	Open						
IRQ5	Open	Open	Closed	Open	Open	Open	Open	Open	Open
í IRQ7	Open	Open	Open	Closed	Open	Open	Open	Open	Open
IRQ9	Open	Open	Open	Open	Closed	Open	Open	Open	Open
IRQ10	Open	Open	Open	Open	Open	Closed	Open	Open	Open
IRQ11	Open	Open	Open	Open	Open	Open	Closed	Open	Open
IRQ12	Open	Closed	Open						
IRQ15	Open	Closed							