
## CREATIVE LABS, INC. SOUNDBLASTER 16 IDE CSP (CT2830 & CT2839) SOUNDBLASTER 16 IDE (CT2830 & CT2839)

Card Type Chip Set Maximum Onboard Memory I/O Options Sound card Creative Technology None Line in connector, microphone in connector, line out connector, speaker out connector, game/MIDI port, CD-ROM audio in connector, CD-ROM interface, PC internal speaker, feature connector 16-bit ISA

## Data Bus



CONNECTIONS			
Function	Label	Function	Label
Line in connector	CN1	CD-ROM audio in connector	CN6
Microphone connector	CN2	Feature connector	CN7
Line out connector	CN3	CD-ROM interface	CN8
Speaker out connector	CN4	CD-ROM audio in connector	CN9
Game/MIDI port	CN5	PC internal speaker	JP25

USER CONFIGURABLE SETTINGS			
Function	Label	Position	
í Factory configured – do not alter	JP14	Unidentified	
í Factory configured – do not alter	JP17	Unidentified	
í MP-401 I/O address select 330	JP18	Closed	
MP-401 I/O address select 300	JP18	Open	
í Factory configured – do not alter	JP26	Unidentified	
í Factory configured – do not alter	JP27	Unidentified	
í Joystick enabled	JYEN	Closed	
Joystick disabled	JYEN	Open	

Continued on next page. . .

## CREATIVE LABS, INC. SOUNDBLASTER 16 IDE CSP (CT2830 & CT2839) SOUNDBLASTER 16 IDE (CT2830 & CT2839)

... continued from previous page

8-BIT DMA CHANNEL SELECTION				
Channel JP19 JP20				
0	Closed	Closed		
í 1	Open	Closed		
3	Closed	Open		

16-BIT DMA CHANNEL SELECTION				
Channel JP21 JP22				
í 5	Closed	Closed		
6	Open	Closed		
7	Closed	Open		

INTERRUPT SELECTION			
IRQ	JP23	JP24	
2	Closed	Closed	
í 5	Open	Closed	
7	Closed	Open	
10	Open	Open	

IDE PORT SELECTION			
Port	JP15	JP16	
Secondary	Closed	Open	
í Tertiary	Open	Closed	
Quaternary	Open	Open	

IDE INTERRUPT SELECTION					
IRQ	JP9	JP10	JP11	JP12	JP13
10	Closed	Open	Open	Open	Open
11	Open	Closed	Open	Open	Open
12	Open	Open	Closed	Open	Open
14	Open	Open	Open	Closed	Open
15	Open	Open	Open	Open	Closed

AUDIO I/O ADDRESS SELECTION			
Address	JP15	JP16	
í 220	Closed	Closed	
240	Open	Closed	
260	Closed	Open	
280	Open	Open	

CSP CHIP SELECTION			
Setting	JP18	JP19	
Enabled	Open	Open	
Disabled	Closed	Closed	