
## JAMECO ELECTRONIC COMPONENTS JE1068

Card Type Multi-I/O card
Chip Set Winbond
Maximum Onboard Memory None

I/O Options game port, parallel port, serial ports (2 Data Bus 8-bit ISA

Card Size Half-length, full-height



CONNECTIONS			
Function	Label	Function	Label
Game port	CN1	Serial port 1	CN3
25-pin parallel port	CN2	Serial port 2	CN4

USER CONFIGURABLE SETTINGS		
Function	Label	Position
í Serial port 1 enabled	JP2	Pins 1 & 2 closed
Serial port 1 disabled	JP2	Pins 2 & 3 closed
í Serial port 2 enabled	JP4	Pins 1 & 2 closed
Serial port 2 disabled	JP4	Pins 2 & 3 closed
í Parallel port enabled	JP6	Pins 1 & 2 closed
Parallel port disabled	JP6	Pins 2 & 3 closed
í Game port enabled	JP7	Pins 1 & 2 closed
Game port disabled	JP7	Pins 2 & 3 closed
í Factory configured - do not alter	JP11	Pins 1 & 2 closed
í Factory configured - do not alter	JP12	Pins 1 & 2 closed

PARALLEL PORT ADDRESS SELECTION	
Setting	JP5
í LPT1 (378h)	Pins 1 & 2 closed
LPT2 (278h)	Pins 2 & 3 closed

SERIAL PORT 1 ADDRESS SELECTION	
Setting	JP1
í COM1 (3F8h)	Pins 1 & 2 closed
COM3 (3E8h)	Pins 2 & 3 closed

## JAMECO ELECTRONIC COMPONENTS JE1068

. . . continued from previous page

SERIAL PORT 2 ADDRESS SELECTION	
Setting	JP3
í COM2 (2F8h)	Pins 1 & 2 closed
COM4 (2E8h)	Pins 2 & 3 closed

SERIAL PORT 1 INTERRUPT SELECTION	
IRQ	JP8
í IRQ4	Pins 1 & 2 closed
IRQ3	Pins 2 & 3 closed

SERIAL PORT 2 INTERRUPT SELECTION	
IRQ	JP9
í IRQ3	Pins 1 & 2 closed
IRQ4	Pins 2 & 3 closed

PARALLEL PORT INTERRUPT SELECTION	
IRQ	JP10
í IRQ7	Pins 1 & 2 closed
IRQ5	Pins 2 & 3 closed