

<b>Platform</b>	INTEL Socket 2011*2
<b>Model Name</b>	AFX79-ETH9EX
<b>Chipset</b>	Intel® C602
<b>CPU Supports (Recommended)</b>	Xeon Processor E5-2603 Xeon Processor E5-4603 Xeon Processor E5-2609 Xeon Processor E5-2603 V2 Xeon Processor E5-4603 V2 Xeon Processor E5-2609 V2 Xeon Processor E5-2620 Xeon Processor E5-2620 V2 Xeon Processor E5-4607 V2 Xeon Processor E5-2618L V2
<b>FSB</b>	1066/1333/1600MHz
<b>Memory</b>	LONGDIMM DDR3 1066/1333/1600MHz
<b>Dimm</b>	1 x Memory Slot (Max. up to 8GB)
<b>Onboard Graphics</b>	Intel® HD Graphics
<b>PCI/PCI-E Slots</b>	9 x PCI Express 3.0 x16 slots (Slot distance 60mm)
<b>SATA</b>	1 x SATA2, 1 x MSATA2
<b>IDE</b>	N/A
<b>Audio</b>	N/A
<b>LAN</b>	Realtek RTL8105/8106 10/100Mbps Ethernet on board
<b>Back Panel I/Os</b>	4 x USB 2.0 Ports
<b>ON-Board Pinheaders/Connectors</b>	1x USB 2.0 pinheader (supports additional 2 USB 2.0s) 4 X FAN(4PIN) 12V 10 X JATX_PWR 12V
<b>BIOS</b>	UEFI BIOS
<b>Form Factor</b>	597mm*195mm
<b>Mounting</b>	10 mounting holes