
DIAMOND FLOWER, INC. 286-12/16E

Processor	8028
Processor Speed	12/1
Chip Set	Head
Max. Onboard DRAM	4MB
Cache	None
BIOS	AMI
Dimensions	220n
I/O Options	None
NPU Options	8028

80286 12/16MHz Headland 4MB None AMI 220mm x 220mm None 80287



CONNECTIONS				
Purpose	Location	Purpose	Location	
External battery	J2	Power LED & Keylock	J14	
Turbo switch	J3/J16	Reset switch	J15	
Auxiliary keyboard	J12	Turbo LED	J17	
Speaker	J13			

Continued on next page . . .

DIAMOND FLOWER, INC. 286-12/16E

... continued from previous page

USER CONFIGURABLE SETTINGS			
Function	Jumper	Position	
í Battery select internal	JP2	pins 2 & 3 closed	
Battery select external	JP2	pins 1 & 2 closed	
í Monitor type select color	JP3	Closed	
Monitor type select monochrome	JP3	Open	
í CPU speed select 12MHz	JP6	pins 1 & 2 closed	
CPU speed select 16MHz	JP6	pins 2 & 3 closed	

DRAM CONFIGURATION		
Size	Bank 0	Bank 1
512KB	(2) 256K x 9	NONE
1MB	(2) 256K x 9	(2) 256K x 9
2MB	(2) 1M x 9	NONE
2.5MB	(2) 256K x 9	(2) 1M x 9
4MB	(2) 1M x 9	(2) 1M x 9

NPU SPEED CONFIGURATION		
Speed	JP7	JP8
8MHz	pins 2 & 5 closed	Closed
10MHz	pins 5 & 6 closed	Closed
12MHz	pins 4 & 5 closed	Open