


DTK COMPUTER, INC.

PEM - 3335D(S)/4035D(S)

Processor	80386DX
Processor Speed	33/40MHz
Chip Set	DTK
Max. Onboard DRAM	16MB (8MB on external memory card)
Cache	64KB
BIOS	AMI/DTK
Dimensions	330mm x 222mm
I/O Options	32-bit external memory card slot (PEI-307)
NPU Options	80387/3167



CONNECTIONS			
Purpose	Location	Purpose	Location
32-bit external memory card	CN1	Turbo switch	J3 pins 1 & 2
Reset switch	J1	Speaker	J4
Turbo LED	J2	Power LED & keylock	J5

Continued on next page . . .

DTK COMPUTER, INC.
P E M - 3 3 3 5 D (S) / 4 0 3 5 D (S)

... continued from previous page

USER CONFIGURABLE SETTINGS		
Function	Jumper/Switch	Position
í CPU speed select switchable from turbo switch	J3	pins 1 & 2 closed
CPU speed select switchable from keyboard	J3	pins 2 & 3 closed
CPU speed select switchable from turbo switch w/cache support	J3	Open
í NPU disabled	J11	Closed
NPU enabled	J11	Open
í Monitor type select monochrome	SW1/4	Off
Monitor type select color	SW1/4	On

DRAM CONFIGURATION		
Size	Bank 0	Bank 1
1MB	(4) 256K x 9	NONE
2MB	(4) 256K x 9	(4) 256K x 9
4MB	(4) 1M x 9	NONE
5MB	(4) 1M x 9	(4) 256K x 9
8MB	(4) 1M x 9	(4) 1M x 9

DRAM SWITCH CONFIGURATION			
Size	SW1/1	SW1/2	SW1/3
1MB	On	On	On
2MB	On	On	On
4MB	On	Off	On
5MB	Off	Off	On
8MB	On	On	Off