

LEADING EDGE PRODUCTS, INC.
MODEL D3/SX (VERSION 2)

... continued from previous page

CONNECTIONS			
Purpose	Location	Purpose	Location
Mouse port	CN1	Parallel port	CN4
Serial port 1 (25 pin)	CN2	Floppy drive interface	CN5
Serial port 2 (9 pin)	CN3		

USER CONFIGURABLE SETTINGS		
Function	JUMPER	Position
í Monitor type select color	J5	pins 1 & 2 closed
Monitor type select monochrome	J5	pins 2 & 3 closed
í Floppy drive interface enabled	J9	pins 2 & 3 closed
Floppy drive interface disabled	J9	pins 1 & 2 closed
í Mouse port enabled	J15	pins 1 & 2 closed
Mouse port disabled	J15	pins 2 & 3 closed

DRAM CONFIGURATION					
Size	Bank 0	Bank 1	J6	J7	J8
512KB	(2) 256K x 9	None	pins 2 & 3	pins 2 & 3	pins 2 & 3
1MB	(2) 256K x 9	(2) 256K x 9	pins 2 & 3	pins 1 & 2	pins 2 & 3
2MB	(2) 1M x 9	NONE	pins 2 & 3	pins 2 & 3	pins 1 & 2
4MB	(2) 1M x 9	(2) 1M x 9	pins 2 & 3	pins 1 & 2	pins 1 & 2

Note: Pins designated should be in the closed position.

PARALLEL PORT CONFIGURATION			
IRQ	ADDRESS	J10	J11
5	378h	pins 1 & 2 closed	pins 2 & 3 closed
7	278h	pins 2 & 3 closed	pins 1 & 2 closed
5	278h	pins 1 & 2 closed	pins 1 & 2 closed
7	378h	pins 2 & 3 closed	pins 2 & 3 closed
Disabled	Disabled	Open	Open

Continued on next page ...

LEADING EDGE PRODUCTS, INC.
MODEL D3/SX (VERSION 2)

... continued from previous page

SERIAL PORT CONFIGURATION			
Port 1 (25 pin)	Port 2 (9 pin)	J12	J13
COM1	COM2	pins 2 & 3 closed	pins 2 & 3 closed
COM1	COM4	pins 2 & 3 closed	pins 1 & 2 closed
COM1	Disabled	pins 2 & 3 closed	Open
COM3	COM2	pins 1 & 2 closed	pins 2 & 3 closed
Disabled	COM2	Open	pins 2 & 3 closed
COM3	COM4	pins 1 & 2 closed	pins 1 & 2 closed
Disabled	COM4	Open	pins 1 & 2 closed
Disabled	Disabled	Open	Open

MOUSE CONFIGURATION		
IRQ	J16 - J18	J19
3	Open	Open
4	Open	Open
5	Open	Open
9	Open	Closed