


ASLAN COMPUTER CORPORATION

S 6 3 0 1 / S 6 4 0 1

Processor 80386SX/CX486SLC
Processor Speed 25/33/40MHz
Chip Set SARC
Max. Onboard DRAM 16MB
Cache None
BIOS AMI
Dimensions 220mm x 163mm
I/O Options None
NPU Options 80387SX



CONNECTIONS			
Purpose	Location	Purpose	Location
External battery	JP1	Turbo LED	JP7
Turbo switch	JP5	Power LED & keylock	JP8
Reset switch	JP6		

Continued next page...

ASLAN COMPUTER CORPORATION

S6301/S6401

... continued from previous page.

USER CONFIGURABLE SETTINGS		
Function	Jumper	Position
í NPU synchronous with CPU	JP3	pins 1 & 2 closed
NPU asynchronous with CPU	JP3	pins 2 & 3 closed
í CPU speed select 25/33 MHz	JP4	pins 2 & 3 closed
CPU speed select 40 MHz	JP4	pins 1 & 2 closed

DRAM CONFIGURATION		
Size	Bank 0	Bank 1
512K	(2) 256K x 9	NONE
1MB	(2) 256K x 9	(2) 256K x 9
1MB	(2) 512K x 9	NONE
2MB	(2) 512K x 9	(2) 512K x 9
2MB	(2) 1M x 9	NONE
4MB	(2) 1M x 9	(2) 1M x 9
8MB	(2) 4M x 9	NONE
16MB	(2) 4M x 9	(2) 4M x 9