
UNIDENTIFIED

386SX-S NON CACHE MAINBOARD MODEL 2

CX486SLC **Processor Processor Speed** 25/33/40MHz Chip Set Unidentified 16MB Max. Onboard DRAM Cache None **BIOS** Unidentified **Dimensions** 220mm x 220mm

I/O Options None **NPU Options** 80387SX



CONNECTIONS				
Purpose	Location	Purpose	Location	
External battery	JP1	Turbo LED	JP7	
Turbo switch	JP5	Power LED & keylock	JP8	
Reset switch	JP6	Speaker	JP9	

Continued next page. . .

UNIDENTIFIED

386SX-S NON CACHE MAINBOARD MODEL 2

. . . continued from previous page

USER CONFIGURABLE SETTINGS				
Function	Jumper	Position		
í Monitor type select color	JP2	Closed		
Monitor type select monochrome	JP2	Open		
í NPU synchronous with CPU	JP3	pins 1 & 2 closed		
NPU asynchronous with CPU	JP3	pins 2 & 3 closed		
í Pipeline mode disabled	JP4	pins 1 & 2 closed		
Pipeline mode enabled	JP4	pins 2 & 3 closed		

DRAM CONFIGURATION				
Size	Bank 0	Bank 1		
512KB	(2) 256K x 9	NONE		
1MB	(2) 256K x 9	(2) 256K x 9		
2MB	(2) 1M x 9	NONE		
4MB	(2) 1M x 9	(2) 1M x 9		
8MB	(2) 4M x 9	NONE		
16MB	(2) 4M x 9	(2) 4M x 9		

CPU SPEED CONFIGURATION				
Speed	JP10	JP11		
25MHz	pins 1 & 2 closed	pins 2 & 3 closed		
33MHz	pins 2 & 3 closed	pins 1 & 2 closed		
40MHz	pins 2 & 3 closed	pins 2 & 3 closed		