## **MAGITRONICS** ISA-386U3PQ

80386DX **Processor Processor Speed** 40MHz Chip Set **UMC** Max. Onboard DRAM 32MB


Cache 64/128/256KB

**BIOS** AMI

**Dimensions** 220mm x 220mm

I/O Options None

**NPU Options** 80387DX/3167



CONNECTIONS				
Purpose	Location	Purpose	Location	
Turbo LED	CON1	Turbo switch	CON4	
Power LED & keylock	CON2	Reset switch	CON5	
Speaker	CON3			

Continued on next page. . .

## **MAGITRONICS** ISA-386U3PQ

. . . continued from previous page

USER CONFIGURABLE SETTINGS				
Function	Jumper	Position		
í NPU disabled	JP1	pins 1 & 2 closed		
NPU enabled	JP1	pins 2 & 3 closed		
í Monitor type select monochrome	JP2	pins 2 & 3 closed		
Monitor type select color	JP2	pins 1 & 2 closed		

	DRAM CONFIGURATION	
Size	Bank 0	Bank 1
1MB	(4) 256K x 9	NONE
2MB	(4) 256K x 9	(4) 256K x 9
4MB	(4) 1M x 9	NONE
5MB	(4) 256K x 9	(4) 1M x 9
8MB	(4) 1M x 9	(4) 1M x 9
16MB	(4) 4M x 9	NONE
20MB	(4) 1M x 9	(4) 4M x 9
32MB	(4) 4M x 9	(4) 4M x 9

CACHE CONFIGURATION				
Size	Bank 0	Bank 1	TAG	
64KB	(4) 8K x 8	(4) 8K x 8	(1) 8K x 8	
128KB	(4) 32K x 8	NONE	(1) 8K x 8	
256KB	(4) 32K x 8	(4) 32K x 8	(1) 32K x 8	

CACHE JUMPER CONFIGURATION				
Size	CJ1	CJ2	CJ3	
64KB	pins 2 & 3 closed	pins 2 & 3 closed	Open	
128KB	pins 1 & 2 closed	Open	Closed	
256KB	pins 1 & 2 closed	pins 1 & 2 closed	Open	