ASPEN SYSTEMS, INC. SUMMIT

Processor Alpha

Processor Speed 266/300/333MHz


Chip Set LSI Max. Onboard DRAM 1024MB Cache 2/4/8/16MB **BIOS** Aspen

Dimensions 330mm x 226mm

32-bit PCI slots (2), 64-bit PCI slots (2), floppy drive interface, parallel port, PS/2 mouse I/O Options

interface, serial ports (2)

NPU Options None



CONNECTIONS				
Purpose	Location	Purpose	Location	
Remote diagnostics	J4	Reset switch	J24	
Speaker	J11	PS/2 mouse interface	J31	
Serial port 2	J12	LED	J90	
Floppy drive interface	J13	LED	J91	
Parallel port	J14	32-bit PCI slots	PC1 & PC2	
Keylock	J18	64-bit PCI slots	PC3 & PC4	
Serial port 1	J20			

Continued on next page. . .

ASPEN SYSTEMS, INC. SUMMIT

. . . continued from previous page

USER CONFIGURABLE SETTINGS				
Function	Jumper	Position		
í Factory configured - do not alter	J25/11	Open		
í Factory configured - do not alter	J25/12	Closed		
í Factory configured - do not alter	J25/13	Open		
í Factory configured - do not alter	J25/14	Open		
í Factory configured - do not alter	J25/15	Open		
128KB mode	J25/16	Closed		
256KB mode	J25/16	Open		

	DRAM CONFIGURATION	
Size	Bank 0	Bank 1
16MB	(4) 1M x 36	NONE
32MB	(4) 1M x 36	(4) 1M x 36
32MB	(4) 2M x 36	NONE
64MB	(4) 2M x 36	(4) 2M x 36
64BMB	(4) 4M x 36	NONE
128M	(4) 4M x 36	(4) 4M x 36
256MB	(4) 8M x 36	NONE
256MB	(4) 8M x 36	(4) 8M x 36
256MB	(4) 16M x 36	NONE
512MB	(4) 16M x 36	(4) 16M x 36
512MB	(4) 32M x 36	NONE
1024MB	(4) 32M x 36	(4) 32M x 36

DRAM JUMPER CONFIGURATION				
Size	J25/1	J25/2		
16MB	Closed	Closed		
32MB	Closed	Closed		
32MB	Open	Open		
64MB	Open	Open		
64BMB	Closed	Open		
128M	Closed	Open		
256MB	Open	Closed		
256MB	Open	Closed		
256MB	Closed	Closed		
512MB	Closed	Closed		
512MB	Open	Open		
1024MB	Open	Open		

DRAM SPEED CONFIGURATION				
Speed J25/3 J25/4				
60ns	Open	Open		
70ns	Closed	Open		
80ns	Open	Closed		

Continued on next page. . .

ASPEN SYSTEMS, INC. SUMMIT

. . . continued from previous page

CACHE CONFIGURATION			
Size Bank 0			
2MB	2MB		
4MB	4MB		
8MB	8MB		
16MB	16MB		

	CACHE JUMPER CONFIGURATION						
Size	J21	J25/5	J25/6	J25/7	J26	J41	J43
2MB	Open	Closed	Open	Open	Open	Open	Open
4MB	Open	Open	Closed	Closed	Open	Open	Closed
8MB	Open	Open	Closed	Open	Open	Closed	Closed
16MB	Closed	Open	Open	Closed	Closed	Closed	Closed

CACHE SPEED CONFIGURATION					
Speed J25/8 J25/9 J25/10					
10ns	Closed	Open	Open		
12ns	Open	Closed	Closed		
15ns	Open	Closed	Open		

CPU SPEED CONFIGURATION					
Speed J9B J9C J9D					
266MHz	Closed	Closed	Closed		
300MHz	Closed	Closed	Open		
333MHz	Closed	Open	Closed		