


SUPER MICRO

P 6 D N F

Processor	Pentium Pro
Processor Speed	150/166/180/200MHz
Chip Set	Intel
Video Chip Set	None
Maximum Onboard Memory	1GB (BEDO/EDO supported)
Maximum Video Memory	None
Cache	256/512KB (on Pentium Pro CPU)
BIOS	AMI
Dimensions	351mm x 305mm
I/O Options	32-bit PCI slots (4), floppy drive interface, green PC connector, IDE interfaces (2), parallel port, PS/2 mouse interface, serial ports (2), IR connector, VRM connectors (2), USB connectors (2)
NPU Options	None



SUPER MICRO**P 6 D N F***... continued from previous page*

CONNECTIONS			
Purpose	Location	Purpose	Location
IDE interface 1	J11	Reset switch	JP21
IDE interface 2	J12	Green PC connector	JP39
Speaker	J22	Buzzer connector	JP89
IDE interface LED	J23	Chassis fan power	JP91
USB connector	J35	Chassis fan power	JP92
USB connector	J36	Chassis fan power	JP93
PS/2 mouse interface	J84	IR connector	JP96
Floppy drive interface	J85	External battery	JP881
Parallel port	J817	32-bit PCI slots	PC1 - PC4
Serial port 1	J818	VRM connector	VRM1
Serial port 2	J824	VRM connector	VRM2
Power LED & keylock	JP20		

USER CONFIGURABLE SETTINGS			
Function	Label	Position	
í Factory configured - do not alter	JP86	Pins 1 & 2 closed	
í Factory configured - do not alter	JP88	Pins 1 & 2 closed	
í Factory configured - do not alter	JP827	Pins 1 & 2 closed	
í Factory configured - do not alter	JP828	Pins 1 & 2 closed	
í Factory configured - do not alter	JP829	Pins 1 & 2 closed	
í Factory configured - do not alter	JP830	Unidentified	
í Factory configured - do not alter	JP831	Unidentified	
í Factory configured - do not alter	JP832	Unidentified	
í Factory configured - do not alter	JP833	Unidentified	
í Factory configured - do not alter	JP13	Pins 2 & 3 closed	
í Factory configured - do not alter	JP15	Pins 2 & 3 closed	
í Factory configured - do not alter	JP22	Unidentified	
í Factory configured - do not alter	JP23	Unidentified	
í Factory configured - do not alter	JP24	Unidentified	
í Factory configured - do not alter	JP26	Open	
í Factory configured - do not alter	JP27	Closed	
í Factory configured - do not alter	JP35	Unidentified	
í Factory configured - do not alter	JP38	Open	
ISA CLK = PCI CLK/4	JP42	Closed	
ISA CLK = PCI CLK/3	JP42	Open	
í Factory configured - do not alter	JP88	Open	
í Factory configured - do not alter	JP90	Open	
í Factory configured - do not alter	JP94	Open	
í Factory configured - do not alter	JP97	Unidentified	
í CMOS memory normal operation	JP880	Pins 1 & 2 closed	
CMOS memory clear	JP880	Pins 2 & 3 closed	

Continued on next page...

SUPER MICRO

P 6 D N F

... continued from previous page

DRAM CONFIGURATION				
Size	Bank 0	Bank 1	Bank 2	Bank 3
8MB	(2) 1M x 36	None	None	None
16MB	(2) 1M x 36	(2) 1M x 36	None	None
16MB	(2) 2M x 36	None	None	None
32MB	(2) 1M x 36			
32MB	(2) 2M x 36	(2) 2M x 36	None	None
32MB	(2) 4M x 36	None	None	None
48MB	(2) 1M x 36	(2) 1M x 36	(2) 2M x 36	(2) 2M x 36
48MB	(2) 2M x 36	(2) 2M x 36	(2) 1M x 36	(2) 1M x 36
64MB	(2) 2M x 36			
64MB	(2) 4M x 36	(2) 4M x 36	None	None
64MB	(2) 8M x 36	None	None	None
80MB	(2) 1M x 36	(2) 1M x 36	(2) 4M x 36	(2) 4M x 36
80MB	(2) 4M x 36	(2) 4M x 36	(2) 1M x 36	(2) 1M x 36
96MB	(2) 2M x 36	(2) 2M x 36	(2) 4M x 36	(2) 4M x 36
96MB	(2) 4M x 36	(2) 4M x 36	(2) 2M x 36	(2) 2M x 36
128MB	(2) 4M x 36			
128MB	(2) 8M x 36	(2) 8M x 36	None	None
128MB	(2) 16M x 36	None	None	None
144MB	(2) 1M x 36	(2) 1M x 36	(2) 8M x 36	(2) 8M x 36
144MB	(2) 8M x 36	(2) 8M x 36	(2) 1M x 36	(2) 1M x 36
160MB	(2) 2M x 36	(2) 2M x 36	(2) 8M x 36	(2) 8M x 36
160MB	(2) 8M x 36	(2) 8M x 36	(2) 2M x 36	(2) 2M x 36
192MB	(2) 4M x 36	(2) 4M x 36	(2) 8M x 36	(2) 8M x 36
192MB	(2) 8M x 36	(2) 8M x 36	(2) 4M x 36	(2) 4M x 36
256MB	(2) 8M x 36			
256MB	(2) 16M x 36	(2) 16M x 36	None	None
256MB	(2) 32M x 36	None	None	None
272MB	(2) 1M x 36	(2) 1M x 36	(2) 16M x 36	(2) 16M x 36
272MB	(2) 16M x 36	(2) 16M x 36	(2) 1M x 36	(2) 1M x 36
288MB	(2) 2M x 36	(2) 2M x 36	(2) 16M x 36	(2) 16M x 36
288MB	(2) 16M x 36	(2) 16M x 36	(2) 2M x 36	(2) 2M x 36
320MB	(2) 4M x 36	(2) 4M x 36	(2) 16M x 36	(2) 16M x 36
320MB	(2) 16M x 36	(2) 16M x 36	(2) 4M x 36	(2) 4M x 36
384MB	(2) 8M x 36	(2) 8M x 36	(2) 16M x 36	(2) 16M x 36
384MB	(2) 16M x 36	(2) 16M x 36	(2) 8M x 36	(2) 8M x 36
512MB	(2) 16M x 36			
512MB	(2) 32M x 36	(2) 32M x 36	None	None
528MB	(2) 1M x 36	(2) 1M x 36	(2) 32M x 36	(2) 32M x 36
528MB	(2) 32M x 36	(2) 32M x 36	(2) 1M x 36	(2) 1M x 36
544MB	(2) 2M x 36	(2) 2M x 36	(2) 32M x 36	(2) 32M x 36
544MB	(2) 32M x 36	(2) 32M x 36	(2) 2M x 36	(2) 2M x 36

Continued on next page...

SUPER MICRO**P 6 D N F***... continued from previous page***DRAM CONFIGURATION (CON'T)**

Size	Bank 0	Bank 1	Bank 2	Bank 3
576MB	(2) 4M x 36	(2) 4M x 36	(2) 32M x 36	(2) 32M x 36
576MB	(2) 32M x 36	(2) 32M x 36	(2) 4M x 36	(2) 4M x 36
640MB	(2) 8M x 36	(2) 8M x 36	(2) 32M x 36	(2) 32M x 36
640MB	(2) 32M x 36	(2) 32M x 36	(2) 8M x 36	(2) 8M x 36
768MB	(2) 16M x 36	(2) 16M x 36	(2) 32M x 36	(2) 32M x 36
768MB	(2) 32M x 36	(2) 32M x 36	(2) 16M x 36	(2) 16M x 36
1GB	(2) 32M x 36			

Note: Board accepts BEDO/EDO memory. Board also accepts x 32 SIMMs.

CACHE CONFIGURATION

Note: 256KB/512KB cache is located on the Pentium Pro CPU.

CPU SPEED SELECTION

Speed	JP29	JP30	JP31	JP32	JP36	JP37
150MHz	Open	Closed	Closed	Closed	Closed	Open
166MHz	Open	Closed	Closed	Closed	Open	Closed
180MHz	Closed	Open	Closed	Closed	Closed	Open
200MHz	Closed	Open	Closed	Closed	Open	Closed

THERMAL CONTROL SELECTION

Turn on temperature	Turn off temperature	JP95
55	51	Pins 1 & 2 closed
62	58	Pins 2 & 3 closed
69	65	Open

Note: Temperature is in Celsius.