

COMPAQ COMPUTER CORPORATION

PROLINEA 5120E

Processor	Pentium
Processor Speed	75/90/100MHz
Chip Set	Unidentified
Video Chip Set	Unidentified
Maximum Onboard Memory	136MB (EDO supported)
Maximum Video Memory	2MB
Cache	256KB
BIOS	Unidentified
Dimensions	254mm x 218mm
I/O Options	Unidentified
NPU Options	None

34372

CONNECTIONS

Note: The location and types of I/O options are unidentified.

USER CONFIGURABLE SETTINGS

Function	Label	Position
í CMOS memory normal operation	P2	Closed
CMOS memory clear	P2	Open
Password enabled	P3	Pins 1 & 2 closed
Password disabled	P3	Pins 2 & 3 closed

DRAM CONFIGURATION

Size	Bank 0	Bank 1	Bank 2
4MB	4MB	None	None
12MB	4MB	(2) 1M x 36	None
20MB	4MB	(2) 2M x 36	None
20MB	4MB	(2) 1M x 36	(2) 1M x 36
28MB	4MB	(2) 2M x 36	(2) 1M x 36
36MB	4MB	(2) 4M x 36	None
36MB	4MB	(2) 2M x 36	(2) 2M x 36
44MB	4MB	(2) 4M x 36	(2) 1M x 36
52MB	4MB	(2) 4M x 36	(2) 2M x 36
68MB	4MB	(2) 8M x 36	None
68MB	4MB	(2) 4M x 36	(2) 4M x 36
76MB	4MB	(2) 8M x 36	(2) 1M x 36
84MB	4MB	(2) 8M x 36	(2) 2M x 36
100MB	4MB	(2) 8M x 36	(2) 4M x 36
136MB	4MB	(2) 8M x 36	(2) 8M x 36

Note: Bank 0 is factory installed and is not configurable. The location is unidentified.

CACHE CONFIGURATION

Note: The location of the cache is unidentified.

VIDEO MEMORY CONFIGURATION

Note: The location of the video memory is unidentified.

Continued on next page. . .

COMPAQ COMPUTER CORPORATION
PROLINEA 5120E

... continued from previous page

CPU SPEED SELECTION				
CPU speed	Clock speed	Multiplier	P5	P11
75MHz	50MHz	1.5x	Pins 2 & 3 closed	Pins 1 & 2 closed
100MHz	50MHz	1.5x	Pins 2 & 3 closed	Pins 2 & 3 closed
120MHz	60MHz	2x	Pins 1 & 2 closed	Pins 2 & 3 closed

TECHNICAL NOTE
Diagram not available.