


**Socket 478
(Pentium 4)**

ASKA® SST-5652ACD

ATI® 9100IGP DDR ATX MOTHERBOARD



DMI COMPLY



Software Bundle



SPECIFICATION : -

- | | |
|--|---|
| Processor | - Intel® Pentium® 4/5 (Prescott) (Socket 478) (533/800MHz FSB) |
| Chip Set | - ATI® RS300 + IXP150/IXP200 |
| BIOS | - Phoenix (Award) PnP Flash ROM BIOS |
| Memory | - Four DDR Sockets Supports up to 2GB (Dual Channel DDR400) |
| Expansion Slot | - One AGP Slot
Five PCI Slots |
| Graphics
(RADEON 9200 (RV280)
DirectX 8.1 core) | - Integrated 128-bit 3D/2D Graphics Engines with DirectX 8.1 hardware support.
- Hardware Motion Compensation and IDCT & Hardware MPEG2 Decode (DVD).
- 8 to 128MB Frame Buffer Shared with System Memory.
- Integrated 24-bit 350MHz RAMDAC.
- Integrated TV Encoder, Macrovision Support, Composite and S-Video Out (Via Cable Adapter), Pal & NTSC Support. |
| AGP Slot | - 8X AGP Slot |
| Audio | - Integrated AC97 Controller with Standard AC97 Codec
- 6 Channel Audio Codec Support (Optional) |
| Lan | - Optional 10/100 Mb/s Lan (Realtek) |
| USB 2.0 | - Integrated in chipset, USB2.0 x 6 |
| IEEE 1394 | - Optional Two IEEE 1394 Firewire Ports (Via Cable Adapter) |
| IDE & Serial ATA-150 | - Integrated ATA100 and Serial ATA-150 Controller |
| Storage & IO Connector | - Two Channels Parallel ATA100 Connector (Support up to 4 Devices)
- Two Channels Serial ATA Ports (Support up to 2 Devices)
- One FDD Port (Support 3 Mode, 1.2/1.44/2.88 MB FDD)
- One Audio Port (Line-in, Line-out, MIC-in)
- One PS/2 Mouse Port
- One PS/2 Keyboard Port
- One Parallel Port
- One/Two Serial Port
- One VGA Port
- Four USB Ports on Back Panel, 2 USB on Header with Optional Cable
- One RJ45 Port |
| Software | - PC-cillin2002 Anti Virus |
| Board Size | - 305mm x 244mm, ATX Form Factor |