## S



- Intel® 440BX



- Intel® Pentium® II/III & Celeron® (66/100Mhz Front Side Bus) (Slot 1 Type). - 233/266/300/333/350/366/400/433/450/466/500/533/550/600/650/667/700MHz or above.

## **SPECIFICATION: -**

Processor

Chip Set













Chip Set	- Intel® 440BX
BIOS	- 2M Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI).
	- IDE AUTO LBA Mode Supports HDDs over 8.4GB.
	- Trend Micro ChipAway Virus Protection.
Cache	- L2 Cache is CPU Built-in.
Memory	- Size up to 384MB
	- Three 168-pins DIMMs
	- DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB.
On Board I/O	- Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33 Channels.
	Twin Headers for Four IDE Devices Including IDE HDDs and CD ROMs.
	- Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.
	- One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Two USB Ports,
	PS/2 Mouse Port, PS/2 Keyboard Port,
Expansion Slot	- Two ISA Bus Slots (One PCI Shared Slot).
	- Five PCI Bus Slots
	- One Accelerated Graphics Port (AGP).
Plug and Play	- Plug and Play Specification 1.1.
	<ul> <li>Plug and Play for DOS®, Windows® 3.x, and Windows® 95.</li> </ul>
PC97/98	- PC97/98 Ready, PC99 Color Connector.
Power Management	- Support SMM, APM and ACPI.
	<ul> <li>Comply to Energy Star "Green PC" Program.</li> </ul>
	- Supports WAKE-ON-LAN (WOL).
	- Supports Modem Ring-in Wake Up.
PCI	- PCI 2.1.
AGP	- AGP 1.0.
VRM	- On Board VRM 8.4.
Battery	- On-board Lithium Battery.
Others	- CPU Frequency Multiplier Jumperless (optional).
	- Alarm Wake-up.

Board Size

All brand names and trademarks mentioned are property of their respective owners. Specifications are subject to change without further notice.

- Bundle "PC-cillin 6" Anti Virus Software

- 173mm x 305mm, ATX Form Factor.