SIot1





SPECIFICATION: -


















Processor

Chip Set

BIOS

Cache

Memory

On Board I/O

- Intel® Pentium® II/III & Celeron® (66/100Mhz Front Side Bus) (Slot 1 Type).
- 233/266/300/333/350/366/400/433/450/466/500/533/550/600/650/667/700MHz or above.

- Intel® 440ZX

- 2M Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI).
- IDE AUTO LBA Mode Supports HDDs over 8.4GB.
- Trend Micro ChipAway Virus Protection.
- L2 Cache is CPU Built-in.
- Size up to 256MB
- Two 168-pins DIMMs
- DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB.
- Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33 Channels.
 Twin Headers for Four IDE Devices Including IDE HDDs and CD ROMs.
 - Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.
 - One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Two USB Ports, PS/2 Mouse Port, PS/2 Keyboard Port,

Expansion Slot - Two ISA Bus Slots (One PCI Shared Slot).

- Four PCI Bus Slots
 - One Accelerated Graphics Port (AGP).
- Plug and Play Plug and Play Specification 1.1.
 - Plug and Play for DOS®, Windows® 3.x, and Windows® 95.
- PC97/98 PC97/98 Ready, PC99 Color Connector.
 Power Management Support SMM, APM and ACPI.
- Power Management Support SMM, APM and ACPI.
 Comply to Energy Star "Green PC" Program.
 - Supports WAKE-ON-LAN (WOL).
 - Supports Modem Ring-in Wake Up.
- PCI PCI 2.1. AGP - AGP 1.0.
- VRM On Board VRM 8.4.
 Battery On-board Lithium Battery.
- Others CPU Frequency Multiplier Jumperless (optional).
 - Alarm Wake-up.
 - Bundle "PC-cillin 6" Anti Virus Software
- Board Size 173mm x 305mm, ATX Form Factor.