## Slot1





## **SPECIFICATION: -**


















Processor

Chip Set

BIOS

Cache

Memory

On Board Sound

**Expansion Slot** 

- Intel® Pentium® II/III & Celeron® (66/100Mhz Front Side Bus) (Slot 1 Type).
- 233/266/300/333/350/366/400/433/450/466/500/533/550/600/650/667/700MHz or above.

- Intel® 440ZX

- 2M Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI).
  - IDE AUTO LBA Mode Supports HDDs over 8.4GB.
  - Trend Micro ChipAway Virus Protection.
  - L2 Cache is CPU Built-in.
  - Size up to 256MB
  - Two 168-pins DIMMs
  - DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB.
- On Board I/O

   Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33 Channels.

  Twin Headers for Four IDE Devices Including IDE HDDs and CD ROMs.
  - Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.
  - One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Two USB Ports,

PS/2 Mouse Port, PS/2 Keyboard Port,
- Creative ES1373 PCI Sound Chip.

- PnP, Creative 3D Enhancement, Wave Synth Wave Table.
- Full-Duplex, Sound Blaster 16 Compatible.
   Line-in Line-out Mic-in and MIDI/Game Port
- Two ISA Bus Slots (One PCI Shared Slot).
- Four PCI Bus Slots
- One Accelerated Graphics Port (AGP).
- Plug and Play Plug and Play Specification 1.1.
  - Plug and Play for DOS®, Windows® 3.x, and Windows® 95.
- PC97/98 PC97/98 Ready, PC99 Color Connector.
- Power Management Support SMM, APM and ACPI.
  - Comply to Energy Star "Green PC" Program.
  - Supports WAKE-ON-LAN (WOL).
  - Supports Modem Ring-in Wake Up.

PCI - PCI 2.1. AGP - AGP 1.0.

VRM - On Board VRM 8.4.
Battery - On-board Lithium Battery.

Others - CPU Frequency Multiplier Jumperless (optional).

- Alarm Wake-up.

- Bundle "PC-cillin 6" Anti Virus Software

Board Size - 173mm x 305mm, ATX Form Factor.