



## **SPECIFICATION: -**

















Processor

Chip Set

Cache

Memory

Plug and Play

- Intel® Pentium® II/III & Celeron® (66/100Mhz Front Side Bus) (Slot 1 Type).
- 233/266/300/333/350/366/400/433/450/466/500/533/550/600/650/667/700MHz or above.
- Intel® 440ZX
- BIOS - 2M Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI).
  - IDE AUTO LBA Mode Supports HDDs over 8.4GB.
  - Anti-Virus Protection.
  - Trend Micro ChipAway Virus Protection.
  - L2 Cache is CPU Built-in.
  - Size up to 256MB.
  - Two 168-pins DIMMs.
- DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB. On Board I/O
  - Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33 Channels. Twin Headers for Four IDE Devices Including IDE HDDs and CD ROMs.
  - Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.
  - One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Two USB Ports, PS/2 Mouse Port, PS/2 Keyboard Port.
- **Expansion Slot** - One ISA Bus Slots (One PCI Shared Slot).
  - Three PCI Bus Slots (One ISA Shared Slot).
  - One Accelerated Graphics Port (AGP). - Plug and Play Specification 1.1.
  - Plug and Play for DOS®, Windows® 3.x, and Windows® 95.
- PC97/98 PC97/98 Ready, PC99 Color Connector.
- Power Management Support SMM, APM and ACPI.
  - Comply to Energy Star "Green PC" Program. Supports WAKE-ON-LAN (WOL).
    - Supports Modem Ring-in Wake Up.
- PCI - PCI 2 1
- AGP - AGP 1.0. VRM On Board VRM 8.4. Battery On-board Lithium Battery.
- Others - CPU Frequency Multiplier Jumperless (optional).
  - Alarm Wake-up.
  - Bundle "PC-cillin 6" Anti Virus Software
- Board Size - 170mm x 244mm, Micro ATX Form Factor.