

INTEL BX ATX MOTHERBOARD



SPECIFICATION: -









Twin Socket





Software Bundle



Processor

Chip Set

RIOS

Cache

Memory

- Intel® Pentium® II/III & Celeron® (66/100Mhz Front Side Bus) (PGA 370 & Slot 1).
- 233/266/300/333/350/366/400/433/450/466/500/533/550/600/650/667/700MHz or above.
- Intel® 440BX
- 2M Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI).
 - IDE AUTO LBA Mode Supports HDDs over 8.4GB.
 - Trend Micro ChipAway Virus Protection.
 - L2 Cache is CPU Built-in.
 - Size up to 384MB
 - Three 168-pins DIMMs
 - DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB.
- On Board I/O - Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33 Channels. Twin Headers for Four IDE Devices Including IDE HDDs and CD ROMs.
 - Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.
 - One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Two USB Ports, PS/2 Mouse Port, PS/2 Keyboard Port,
- **Expansion Slot** - Two ISA Bus Slots (One PCI Shared Slot).
 - Five PCI Bus Slots
 - One Accelerated Graphics Port (AGP).
- Plug and Play - Plug and Play Specification 1.1.
 - Plug and Play for DOS®, Windows® 3.x, and Windows® 95.
- PC97/98 - PC97/98 Ready, PC99 Color Connector. Power Management - Support SMM, APM and ACPI.
 - Comply to Energy Star "Green PC" Program.
 - Supports WAKE-ON-LAN (WOL).
 - Supports Modem Ring-in Wake Up.
- PCI PCI 2.1.
- AGP AGP 1.0. VRM On Board VRM 8.4.
- Battery On-board Lithium Battery. Others CPU Frequency Multiplier Jumperless (optional).
 - Alarm Wake-up.
 - Bundle "PC-cillin 6" Anti Virus Software
- Board Size - 200mm x 305mm, ATX Form Factor.