
157 SST-5830

VIA APOLLO PRO BAT MOTHERBOARD



SPECIFICATION: -

On Board I/O









Socket 370









Processor - Intel® Pentium® III, Celeron (66/100Mhz Front Side Bus) (PGA 370 Type).

- 300/333/350/366/400/433/450/466/500/533/550/600/650/667/700MHz or above.

Chip Set VIA® Apollo Pro.

BIOS 2M Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI).

- IDE AUTO LBA Mode Supports HDDs over 8.4GB.

- Trend Micro ChipAway Virus Protection.

L2 Cache is CPU Built-in.

- Up to 512MB.

- Two 168-pins DIMMs (64bit).

Synchronous DRAM (SDRAM).

- DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB.

- Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33 Channels.

Twin Headers for Four IDE Devices Including IDE HDDs and CDROMs.

- Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.

- One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Two USB Ports.

PS/2 Mouse Port, PS/2 Keyboard Port.

Two ISA Bus Slots. **Expansion Slot**

- Three PCI Bus Slots.

One Accelerated Graphics Port (AGP).

Plug and Play - Plug and Play Specification 1.1.

- Plug and Play for DOS®, Windows® 3.x, and Windows® 95.

- PC97/98 Ready PC97/98 **Power Management** - Support SMM & APM.

- Comply to Energy Star "Green PC" Program.

PCI - PCI 2.1. AGP - AGP 1.0.

VRM - On Board VRM 8.4. Others - On-board Lithium Battery.

- Bundle "PC-cillin 6" Anti Virus Software

Board Size - 220mm x 195mm, Baby AT Form Factor.

All brand names and trademarks mentioned are property of their respective owners. Specifications are subject to change without further notice.