


Socket A

ASMA[®] SST-5856ABD VIA[®] KT-333 DDR ATX MOTHERBOARD



SPECIFICATION : -

Processor	- AMD [®] Athlon [®] & Duron [®] (K7) (333MHz DDR Front Side Bus) (Socket A).
Chip Set	- VIA [®] KT-333 + 8233.
BIOS	- Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI). - IDE AUTO LBA Mode Supports HDDs over 8.4GB. - Trend Micro ChipAway Virus Protection.
Cache	- L2 Cache is CPU Built-in.
Memory	- Three DDR Socket Support up to 1.5G (DDR266/333).
On Board I/O	- Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33/66/100 Channels. Twin Headers for Four IDE Devices Including IDE HDDs and CDROMs. - Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB. - One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, - Six USB Ports (on board 2 USB ports by 8233A) (Four USB Ports by Optional Adapter Cable - 2 USB ports by 8233A), PS/2 Mouse Port, PS/2 Keyboard Port.
On Board Sound	- Integrated hardware accelerated AC97 Controller with Standard AC97 Codec. - PnP, Full-Duplex, Sound Blaster 16 Compatible, Direct Sound Ready. - Line-in, Line-out, Mic-in and MIDI/Game Port .
Expansion Slot	- Five PCI Bus Slots. - One Accelerated Graphics Port (AGP). - One ACR.
Plug and Play	- Plug and Play Specification 1.1. - Plug and Play for DOS [®] , Windows [®] 3.x, and Windows [®] 95/98/2000/XP.
PC97/98	- PC97/98 Ready, PC99 Color Connector.
Power Management	- Support SMM, APM and ACPI. - Comply to Energy Star "Green PC" Program. - Supports Modem Ring-in Wake Up.
PCI	- PCI 2.1.
AGP	- AGP 2.0 / 1.0.
VRM	- On Board VRM.
Battery	- On-board Lithium Battery.
Others	- Alarm Wake-up - Bundle "PC-cillin" Anti Virus Software
Board Size	- ATX Form Factor.



DMI COMPLY



Software Bundle

