

Socket A

ASKA[®] SST-5858ABD VIA[®] KT-400A DDR ATX MOTHERBOARD



SPECIFICATION : -



DMI COMPLY



Software Bundle



Processor	- AMD [®] Athlon [®] & Duron [®] (K7) (266/333MHz FSB) (Socket A).
Chip Set	- VIA [®] KT-400A + 8235.
BIOS	- Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI). - Trend Micro ChipAway Virus Protection.
Cache	- L2 Cache is CPU Built-in.
Memory	- Three DDR Socket Support up to 1.5G (DDR266/333/400).
On Board I/O	- Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33/66/100/133 Channels. Twin Headers for Four IDE Devices Including IDE HDDs and CDROMs. - Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB. - One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Six USB 2.0 Ports (Four USB Ports by Optional Adapter Cable), PS/2 Mouse Port, PS/2 Keyboard Port.
On Board Sound	- Integrated hardware accelerated AC97 Controller with Standard AC97 Codec. - PnP, Full-Duplex, Sound Blaster 16 Compatible, Direct Sound Ready. - Line-in, Line-out, Mic-in and MIDI/Game Port. - Optional 6 Channel Audio Codec Support
On Board Lan (Optional)	- 10/100 Mb/s Lan (VIA).
Expansion Slot	- Five PCI Bus Slots. - One Accelerated Graphics Port (8X AGP).
Plug and Play	- Plug and Play Specification 1.1. - Plug and Play for DOS [®] , Windows [®] 3.x, and Windows [®] 95/98/2000/XP.
PC97/98	- PC97/98 Ready, PC99 Color Connector.
Power Management	- Support SMM, APM and ACPI. - Comply to Energy Star "Green PC" Program. - Supports Modem Ring-in Wake Up.
PCI	- PCI 2.1.
AGP	- AGP 2.0 / 1.0.
VRM	- On Board VRM.
Battery	- On-board Lithium Battery.
Others	- Alarm Wake-up - Bundle "PC-cillin" Anti Virus Software
Board Size	- 305mm x 220mm, ATX Form Factor.