


SOCKET 370

ASKA[®] SST-5872AP VIA PM133 (8605) ATX MOTHERBOARD



SPECIFICATION : -

Processor	- Intel® Pentium® III & Celeron® (66/100133Mhz Front Side Bus)(PGA 370 Type).
Chip Set	- VIA® PM133 (8605 + 686A / 686B).
BIOS	- 2M Flash EPROM (Support PnP, APM, ATAPI). - IDE AUTO LBA Mode Supports HDDs over 8.4GB. - Trend Micro ChipAway Virus Protection.
Cache Memory	- L2 Cache is CPU Built-in. - Up to 768MB.
On Chip AGP (Savage4)	- Three 168-pins DIMMs (64bit). - AGP Compliant. - Transfer Rate up to 533MB/sec. - 64-bit Single Cycle 2D/3D Graphic Engines. - Support 4 to 8MB Frame Buffer Shared with System Memory. - Integrated 24-bit 230MHz RAMDAC. - Resolution up to 1600 x 1200. - DirectX6 & OpenGL API.
On Board I/O	- Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33/66/100 Channels. Twin Headers for Four IDE Devices Including IDE HDDs and CDROMs - Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB. - One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Four USB Ports, PS/2 Mouse Port, PS/2 Keyboard Port.
On Board Sound	- AC97 Audio Controller with Standard AC97 Codec. - PnP, Full-Duplex, Sound Blaster Pro, Direct Sound Ready. - Line-in, Line-out, Mic-in and MIDI/Game Port.
Expansion Slot	- One AGP Bus Slot (4X). - One ISA Slot. - Five PCI Bus Slots. - One Audio Modem Riser (AMR).
Plug and Play	- Plug and Play Specification 1.0A. - Plug and Play for DOS®, Windows® 3.x, and Windows® 95/98.
PC97/98	- PC97/98 Ready, PC99 Color Connector.
Power Management	- Support SMM, APM and ACPI. - Comply to Energy Star "Green PC" Program. - Supports Modem Ring-in Wake Up.
PCI	- PCI 2.1.
AGP	- AGP 2.0 / 1.0.
VRM	- On Board VRM 8.4.
Battery	- On-board Lithium Battery.
Others	- CPU Frequency Multiplier Jumperless (Optional) - Alarm Wake-up. - Bundle "PC-cillin" Anti Virus Software.
Board Size	- Support Intel Type C Standard Heat Sink for 1G or above Pentium III CPU. - 305mm x 218mm, ATX Form Factor.



DMI COMPLY



Software Bundle

