157 SST-5882

VIA APOLLO PRO133 BABY AT MOTHERBOARD



SPECIFICATION: -

BIOS

Cache

Memory

On Board I/O

Expansion Slot









Software Bundle



- Intel® Pentium® II/III & Celeron® (66/100Mhz Front Side Bus) (Slot 1 Type) . Processor

233/266/300/333/350/366/400/433/450/466/500/533/550/600/650/667/700MHz or above.

Chip Set - VIA® Apollo PRO133 (693A + 596A or 596B).

- 2M Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI).

- IDE AUTO LBA Mode Supports HDDs over 8.4GB.

Trend Micro ChipAway Virus Protection.

L2 Cache is CPU Built-in.

- Size up to 512MB.

- Two 168-pins DIMMs.

- Synchronous DRAM (SDRAM).

DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB.

Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33/66 (596B ver. only & Optional Ultra DMA 66 Cable) Channels. Twin Headers for Four IDE Devices Including IDE HDDs and CDROMs.

Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.

One ECP/EPP Parallel Port. Two 16550A UART Serial Ports.

Two USB Ports (Optional Adapter Cable).

- PS/2 Mouse Port (Optional Adapter Cable). Keyboard Port.

- IrDA Port (Optional TX/RX Module).

Two ISA Bus Slots (One PCI Shared Slot).

Three PCI Bus Slots (One ISA Shared Slot).

One Accelerated Graphics Port (AGP). Plug and Play Plug and Play Specification 1.1.

- Plug and Play for DOS®, Windows® 3.x, and Windows® 95.

PC97/98 PC97/98 Ready.

Support SMM, APM and ACPI. Power Management

Comply to Energy Star "Green PC" Program.

Supports Modem Ring-in Wake Up.

PCI PCI 2.1. AGP AGP 1.0.

- On Board VRM 8.2. VRM On-board Lithium Battery. Battery

CPU Frequency Multiplier Jumperless (Optional). Others

- Alarm Wake-up

Bundle "PC-cillin 6" Anti Virus Software **Board Size** - 200mm x 220mm, Baby AT Form Factor.