Socket 370



VIA APOLLO PRO133 ATX MOTHERBOARD



SPECIFICATION: -

BIOS

Cache

Memory

On Board I/O

Plug and Play











Software Bundle



Processor - Intel® Pentium® III & Celeron® (66/100/133Mhz Front Side Bus) (PGA370 Type).

300/333/350/366/400/433/450/466/500/533/550/600/650/667/700MHz or above.

VIA® Apollo Pro133 (686A + 693A). Chip Set

2M Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI).

IDE AUTO LBA Mode Supports HDDs over 8.4GB.

- Trend Micro ChipAway Virus Protection.

- L2 Cache is CPU Built-in.

- Size up to 768MB.

Three 168-pins DIMMs.

Synchronous DRAM (SDRAM).

DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB.

Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33/66 Channels (Optional Ultra DMA 66 Cable). Twin Headers for Four IDE Devices Including IDE HDDs and CDROMs.

- Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.

One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Two USB Ports, PS/2 Mouse Port. PS/2 Keyboard Port.

On Board Sound Integrated AC97 Controller with Standard AC97 Codec.

PnP, Full-Duplex, Sound Blaster 16 Compatible, Direct Sound Ready.

Line-in, Line-out, Mic-in and MIDI/Game Port .

Two ISA Bus Slots (One PCI Shared Slot). **Expansion Slot** Four PCI Bus Slots (One ISA Shared Slot).

One Accelerated Graphics Port (AGP).

One Audio Modem Riser (AMR). Plug and Play Specification 1.1.

Plug and Play for DOS®, Windows® 3.x, and Windows® 95.

PC97/98 PC97/98 Ready, PC99 Color Connector.

Power Management Support SMM, APM and ACPI.

Comply to Energy Star "Green PC" Program. Supports Modem Ring-in Wake Up.

PCI - PCI 2.1. AGP - AGP 1.0.

VRM - On Board VRM 8.4. Battery On-board Lithium Battery.

Others CPU Frequency Multiplier Jumperless (Optional).

Alarm Wake-up

Bundle "PC-cillin 6" Anti Virus Software

Board Size ATX Form Factor.

All brand names and trademarks mentioned are property of their respective owners. Specifications are subject to change without further notice.