## Socket 478 (Pentium 4)





VIA® P4M266A + VT8235

L2 Cache is CPU Built-in.

Size up 1GB (PC133). Two DIMM Sockets.

Support PnP, APM, ACPI, ATAPI, DMI.

Trend Micro ChipAway Virus Protection.

## **SPECIFICATION: -**















Software Bundle



Processor Chip Set BIOS

Cache Memory

On Board I/O

On Board Sound

Others

**Board Size** 

On Chip AGP (Savage4)

AGP Compliant.

Transfer Rate up to 533MB/sec.

64-bit Single Cycle 2D/3D Graphic Engines.

Support 4 to 32MB Frame Buffer Shared with System Memory. Integrated 24-bit 230MHz RAMDAC.

Intel® Pentium® 4 (mPGA 478 Socket Type) (533MHz Front Side Bus).

Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33/66/100/ 133 Channels. Twin Headers for Four IDE Devices Including IDE HDDs and

One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Six USB 2.0 Ports (Four USB Ports by Optional Adapter Cable), PS/2 Mouse Port, PS/2 Keyboard

Support Two FDDs of 360KB, 720KB, 1,2MB, 1,44MB or 2,88MB.

Resoluction up to 1600 x 1200.

DirectX6 & OpenGL API.

Integrated AC97 Controller with Standard AC97 Codec.

PnP, Full-Duplex, Sound Blaster and Direct Sound Ready.

Line-in, Line-out, Mic-in and MIDI/Game Port. Optional 6 Channel Audio Codec Support

On Board Lan (Optional) 10/100 Mb/s Lan (RT8100B).

**Expansion Slot** Three PCI Bus Slots.

One Accelerated Graphics Port (AGP). Plug and Play

Plug and Play Specification 1.0A.

Plug and Play for DOS®, Windows® 3.x, and Windows® 95/98.

PC97/98 PC97/98 Ready, PC99 Color Connector. **Power Management** Support SMM, APM and ACPI.

Comply to Energy Star "Green PC" Program.

Supports Modem Ring-in Wake Up.

PCI PCI 2.1. AGP AGP 2.0 / 1.0. **VRM** On Board VRM 9.0. Batterv On-board Lithium Battery.

Alarm Wake-up.

Bundle "PC-cillin" Anti Virus Software. 244mm x 224mm, Micro ATX Form Factor.

All brand names and trademarks mentioned are property of their respective owners. Specifications are subject to change without further notice.