


Twin Socket

ASKA®

SST-6817AT INTEL 810 ATX MOTHERBOARD



SPECIFICATION : -

Processor	<ul style="list-style-type: none"> - Intel® Pentium® II/III & Celeron® (66/100Mhz Front Side Bus) (Slot 1 Type & PGA 370 Type). - 233/266/300/333/350/366/400/433/450/466/500/533/550/600/650/667/700MHz or above.
Chip Set	<ul style="list-style-type: none"> - Intel® 810
BIOS	<ul style="list-style-type: none"> - Intel® Firmware Hub (With Security Feature) (4M bit). - Support PnP, APM, ACPI, ATAPI, DMI. - IDE AUTO LBA Mode Supports HDDs over 8.4GB. - Trend Micro ChipAway Virus Protection.
Cache	<ul style="list-style-type: none"> - L2 Cache is CPU Built-in.
Memory	<ul style="list-style-type: none"> - Size up to 256MB or 512MB (using 128MB Technology). - Two 168-pins DIMMs. - DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB.
On Chip Graphic Engine	<ul style="list-style-type: none"> - Integrated 64-bit 3D/2D Graphic Engines (Intel 752 Core) - Hardware Motion Compensation for S/W MPEG2 Decode (DVD). - Dynamic Video Memory Technology and Optional 4MB Display Cache. - Integrated 24-bit 230MHz RAMDAC. - Resolution up to 1600 x 1200 - DirectX6 & OpenGL API Support - Win 95vxd, Win98/NT5 Mini Port Driver Support.
On Board I/O	<ul style="list-style-type: none"> - Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33 Channels (Optional Ultra DMA 66 & Ultra DMA 66 Cable). Twin Headers for Four IDE Devices Including IDE HDDs and CDROMs. - Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB. - One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Two USB Ports, PS/2 Mouse Port, PS/2 Keyboard Port.
On Board Sound	<ul style="list-style-type: none"> - Integrated AC97 Controller with Standard AC97 Codec. - PnP, Full-Duplex, Sound Blaster and Direct Sound Ready. - Line-in, Line-out, Mic-in and MIDI/Game Port .
Expansion Slot	<ul style="list-style-type: none"> - Five PCI Bus Slots. - One ISA Bus Slot (Optional). - One Audio Modem Riser (AMR).
Plug and Play	<ul style="list-style-type: none"> - Plug and Play Specification 1.1. - Plug and Play for DOS®, Windows® 3.x, and Windows® 95/98.
PC97/98	<ul style="list-style-type: none"> - PC97/98 Ready, PC99 Color Connector.
Power Management	<ul style="list-style-type: none"> - Support SMM, APM and ACPI. - Comply to Energy Star "Green PC" Program. - Supports WAKE-ON-LAN (WOL). - Suspend to RAM (STR) (Optional).
PCI	<ul style="list-style-type: none"> - PCI 2.1.
VRM	<ul style="list-style-type: none"> - On Board VRM 8.4.
Battery	<ul style="list-style-type: none"> - On-board Lithium Battery.
Others	<ul style="list-style-type: none"> - CPU Speed Jumperless. - Alarm Wake-up - Bundle "PC-cillin 6" Anti Virus Software
Board Size	<ul style="list-style-type: none"> - 173mm x 305mm, ATX Form Factor.



DMI COMPLY



Software Bundle

