

Socket 370

ASKA® SST-6818AP INTEL 815 ATX MOTHERBOARD



SPECIFICATION : -

Processor	<ul style="list-style-type: none">- Intel® Pentium® III (100/133Mhz Front Side Bus) (PGA370 Type).- 450MHz or above.
Chip Set	<ul style="list-style-type: none">- Intel® 815.
BIOS	<ul style="list-style-type: none">- Intel Firmware Hub (with Security Feature) (4MB).- Support PnP, APM, ACPI, ATAPI, DMI.- IDE AUTO LBA Mode Supports HDDs over 8.4GB.- Trend Micro ChipAway Virus Protection.
Cache Memory	<ul style="list-style-type: none">- L2 Cache is CPU Built-in.- Size up 768MB.
4X AGP VGA On Chip	<ul style="list-style-type: none">- Three 168-pin DIMMS (64-bit).- Integrated 64-bit 3D/2D Graphic Engines.- Hardware Motion Compensation for S/W MPEG2 Decode (DVD).- Dynamic Video Memory Technology and Optional 4MB Display Cache.- Integrated 24-bit 230MHz RAMDAC.- Resolution up to 1600 x 1200.- DirectX6 & OpenGL API Support.- Win 95vxd, Win98/NT5 Mini Port Driver Support.
On Board I/O	<ul style="list-style-type: none">- Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33/66 Channels (Optional Ultra DMA 66 Cable). Twin Headers for Four IDE Devices Including IDE HDDs and CDROMs.
On Board Sound	<ul style="list-style-type: none">- Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.- One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Two USB Ports, PS/2 Mouse Port, PS/2 Keyboard Port,- Integrated AC97 Controller with Standard AC97 Codec.- PnP, Full-Duplex, Sound Blaster and Direct Sound Ready.
Expansion Slot	<ul style="list-style-type: none">- Line-in, Line-out, Mic-in and MIDI/Game Port .- Five PCI Bus Slots.- One Accelerated Graphics Port (AGP).- One Audio Modem Riser (AMR).
Plug and Play	<ul style="list-style-type: none">- Plug and Play Specification 1.1.- Plug and Play for DOS®, Windows® 3.x, and Windows® 95/98.
PC97/98	<ul style="list-style-type: none">- PC97/98 Ready, PC99 Color Connector.
Power Management	<ul style="list-style-type: none">- Support SMM, APM and ACPI.- Comply to Energy Star "Green PC" Program.- Supports WAKE-ON-LAN (WOL).- Supports Modem Ring-in Wake Up.
PCI	<ul style="list-style-type: none">- PCI 2.1.
AGP	<ul style="list-style-type: none">- AGP 2.0 / 1.0.
VRM	<ul style="list-style-type: none">- On Board VRM 8.4.
Battery	<ul style="list-style-type: none">- On-board Lithium Battery.
Others	<ul style="list-style-type: none">- CPU Speed Jumperless.- Alarm Wake-up.
Board Size	<ul style="list-style-type: none">- Bundle "PC-cillin 6" Anti Virus Software.- 213mm x 305mm, ATX Form Factor.



DMI COMPLY



Software Bundle

