

















Software Bundle



## **SPECIFICATION: -**

4X AGP VGA On Chip

BIOS

Processor Intel® Pentium® III & Celeron® (66/100/133Mhz Front Side Bus) (PGA370 Type). Chip Set

Intel Firmware Hub (with Security Feature).

Support PnP, APM, ACPI, ATAPI, DMI.

IDE AUTO LBA Mode Supports HDDs over 8.4GB.

Trend Micro ChipAway Virus Protection.

L2 Cache is CPU Built-in. Cache Memory

Size up 512MB.

Two 168-pin DIMMS (64-bit).

Integrated 64-bit 3D/2D Graphic Engines.

Hardware Motion Compensation for S/W MPEG2 Decode (DVD).

Dynamic Video Memory Technology and Optional 4MB Display Cache.

Integrated 24-bit 230MHz RAMDAC. Resolution up to 1600 x 1200.

DirectX6 & OpenGL API Support.

Win 95vxd, Win98/NT5 Mini Port Driver Support.

On Board I/O Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33/66

Channels (Optional Ultra DMA 66 Cable). Twin Headers for Four IDE Devices Including IDE, HDDs and CDROMs.

Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.

One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Two USB Ports, PS/2 Mouse Port, PS/2 Keyboard Port,

On Board Sound Integrated AC97 Controller with Standard AC97 Codec. PnP, Full-Duplex, Sound Blaster and Direct Sound Ready.

Line-in, Line-out, Mic-in and MIDI/Game Port .

**Expansion Slot** Two PCI Bus Slots. One Accelerated Graphics Port (AGP).

One Audio Modem Riser (AMR).

Plug and Play Plug and Play Specification 1.1. Plug and Play for DOS®, Windows® 3.x, and Windows® 95/98.

PC97/98 PC97/98 Ready, PC99 Color Connector.

Support SMM, APM and ACPI. **Power Management** 

Comply to Energy Star "Green PC" Program.

Supports WAKE-ON-LAN (WOL).

Supports Modem Ring-in Wake Up.

PCI PCI 2 1 AGP AGP 2.0 / 1.0. VRM On Board VRM 8.4.

Battery On-board Lithium Battery. Others CPU Speed Jumperless.

Bundle "PC-cillin" Anti Virus Software.

Support Intel Type C Standard Heat Sink for 1G or above Pentium III CPU.

**Board Size** 21.4cm x 24.4cm, Micro ATX Form Factor.