



*j@j@A36j@Mainj@board*

<b>Model</b>	432X-XX	442X-XX
<b>Main Board</b>	"A36 V4.x" all-in-one main board	
<b>CPU</b>	386SX	486SLC/486SLC2
<b>Co-processor</b>	NONE	
<b>Internal Cache</b>	NONE	1KB
<b>External Cache</b>	NONE	
<b>SYSTEM RAM</b>	1/2/4/8/16 MB(30 pins SIMM Module)	
<b>BIOS</b>	AWARD	
<b>Core Logic</b>	ACER "ALI M1217" AT / 386 chip	
<b>VIDEO DISPLAY</b>	SVGA 640x480, 800x600, 1024x768	
<b>Video RAM</b>	256KB standard, expandable to 1MB	
<b>Video Control Chip</b>	Trident 8900D-R	
<b>Video Display port</b>	15-pin D-SUB female connector	
<b>HDD/FDD controller</b>	Winbond W83757F Super I/O chip	
<b>I/O Port</b>	2 x 9-pin D-SUB Serial Ports connector, 1 x 25-pin D-SUB Parallel Port connector	
<b>Expansion Slot on board</b>	1 x 16-bit ISA Bus slot	
<b>System Expansion slot</b>	2 x 16-bit ISA Bus slot	