

# NuPRO-860 Series

Full-Size Pentium® M ePCI-X SBC with VGA/GbE/S-ATA/USB 2.0



## Features

- Pentium® M or Celeron® M Processor, low power consumption
- Longevity Intel 855GME chipset, 400MHz FSB
- Maximum 2GB DDR RAM
- VGA, LVDS GbE, USB 2.0, IDE, S-ATA, AC97 Audio, & WDT
- With ATX power connector for backplane-less applications

## Ordering Information

NuPRO-860-P1600/512	PICMG 1.2 Full-size Pentium M SHB, 855GME/6300ESB w/VGA/GbE/S-ATA/Pentium M 1.6GHz/512MB DDR333
NuPRO-860-C1300/512	PICMG 1.2 Full-size Pentium M SHB, 855GME/6300ESB w/VGA/GbE/S-ATA/Celeron M 1.3GHz/512MB DDR333
NuPRO-860-P1100/512	PICMG 1.2 Full-size Pentium M SHB, 855GME/6300ESB w/VGA/GbE/S-ATA/Pentium M 1.1GHz/512MB DDR333

Note: Call for availability of CPU and memory options

## Specifications

### CPU / Core Logic

CPU	Pentium M processors, 1.1GHz-2.0GHz Celeron M processors, 600MHz-1.3GHz
FSB	400MHz
Chipset	Intel 855GME chipset including GMCH, 6300ESB (HanceRapids), FWB
RAM	Two DDR SO-DIMM sockets, supports DDR266/333 up to 2GB
BIOS	Award 4Mb flash memory

### Bus

BusA	ePCI-X Bus-A compliant with PCI-X 66MHz
BusB	ePCI-X Bus-B compliant with PCI 32/33

### I/O Interfaces

IDE	ATA-100, dual channels
Serial ATA	Supports 2 channels SATA-150
USB	2 USB ports on the faceplate, 2 by pin header Compliant with USB Specification Rev. 2.0, individual over-current protection
Super I/O	One UART compatible RS-232 COM ports with ESD protection to 2KV
Audio	Integrated Audio Controllers with AC'97 interface, with optional DB-AC97S daughter board
Watchdog Timer	Built-in 6300ESB, supports 2-stage WDT

### VGA

Display	Built-in with 855GME. 350MHz integrated 24-bit RAMDAC supports standard progressive scan analog monitor with pixel resolution up to 1600 x 1200 at 85MHz and 2048 x 1536 at 75MHz. One DVI interface supports up to 165 Mpixels/sec, resolutions up to 1600x1200 UXGA display. One channel LFP transmitter interface to support LVDS LCD panel resolutions up to UXGA
---------	---

### Ethernet

Ethernet	Intel 82541GI Ethernet controller Support 1000Base-TX, 100Base-TX and 10Base-T (IEEE802.3, 802.3u, and 802.3ab)
Features	Intel PXE pre-boot on Ethernet

### Mechanical and Environmental

Form Factor	Standard Full-size ePCI-X SHB PICMG 1.2
Dimensions	338mm x 122mm (L x W)
Operating Temp.	0 to 60°C
Storage Temp.	-20 to 80°C
Compliance	CE, FCC Class A