

Model: AM-545+

VIA® VP-X Chipset PCI Motherboard

Technical Specifications

CPU

Intel Pentium® (P54C) at 90-233MHz Intel Pentium® MMX[™] (P55C) AMD® K5, K6 Cyrix®/IBM® 6x86/6x86L/MX IDT C6

Cache Memory

Onboard 512KB Pipelined Burst Synchronous L2 Cache

Chipset

VIA® VPX

BIOS

1MB Flash EPROM IDE AUTO LBA Mode Supports HDDs over 6.4GB Anti-Virus Protection

System Memory

2x168-pin DIMMs 2x72-pin SIMMs Supports SDRAM & 3.3V EDO Up to 256MB

Expansion Slots

2xISA Bus Slots 3xPCI Bus Slots

Onboard I/O

Support Two PCI EIDE PIO Mode3, Mode4 & Ultra DMA 33 HDDs Twin Headers for Four IDE Device Support Two FDDs One ECP/EPP Parallel Port, Two 16550 UART Serial Ports, Two USB Ports (Optional Adapter Cable) PS/2 Mouse Port (Optional Adapter Cable), Keyboard Port, IrDA Port (Optional TX/RX Module)

Onboard Sound (Optional)

3D Sound Pro Chipset support HRTF Positional Audio Direct Sound & Software Wavetable Synthesizer, Digital Audio Interface (SPDIF IN/OUT) Supports SB16, WSS & Game

Plug and Play

Plug and Play Specification 1.1 Plug and Play for DOS®, Windows® 3.x and Windows® 95

Other Features

PC97/98 Ready Supports SMM, APM and ACPI Comply to Energy Star "Green PC" Program

All brand names and registered trademarks mentioned are property of their owners