



**Model: AM-662**

## VIA® Apollo Pro Chipset Baby AT Motherboard



[BIOS Upgrade \(8/99\)](#)

### Technical Specifications

#### Processor

- Intel® Pentium II/III & Celeron.
- 233/266/300/333/350/400/450/500MHz or above. (66/100MHz Front Side Bus).

#### Chip Set

- VIA® Apollo Pro.

#### BIOS

- 2M Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI).
- IDE AUTO LBA Mode Supports HDDs over 8.4GB.
- Anti-Virus Protection.

#### Cache

- L2 Cache is CPU Built-in.

#### Memory

- Up to 512MB.
- Two 168-pins DIMMs (64bit).
- Synchronous DRAM (SDRAM).
- DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB.

#### On Board I/O

- Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33 HDDs. Twin Headers for Four IDE Devices Including IDE HDDs and CD ROMs.
- Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.
- One ECP/EPP Parallel Port.
- Two 16550A UART Serial Ports.
- Two USB Ports (Optional Adapter Cable).
- PS/2 Mouse Port (Optional Adapter cable)
- AT Keyboard Port.
- IrDA Port (Optional TX/RX Module).

#### On Board Sound (Optional)

- Creative VIBRA 16XV.
- PnP, Creative 3D Enhancement, Wave Synth Wave Table.
  - Full-Duplex, Sound Blaster 16 Compatible.
- Line-in, Line-out, Mic-in and MIDI/Game Port (via Cable).

#### **Expansion Slot**

- Two ISA Bus Slots.
- Three PCI Bus Slots.
- One Accelerated Graphics Port (AGP).

#### **Plug and Play**

- Plug and Play Specification 1.1.
- Plug and Play for DOS®, Windows® 3.x, and Windows® 95.

#### **PC97/98**

- PC97/98 Ready.

#### **Power Management**

- Support SMM & APM.
- Comply to Energy Star “Green PC” Program.

#### **PCI**

- PCI 2.1 Compliant.

#### **AGP**

- AGP V1.0

#### **VRM**

- On Board VRM 8.2.

#### **Battery**

- On-board Lithium Battery.

#### **Board Size**

- 195mm x 220mm, Baby AT Form Factor.

All brand names and registered trademarks mentioned are property of their owners

---