



***Model: AM-726***

## **PC100 BXcel Pentium®-II Motherboard**



[BIOS Update](#)

---

### *Technical Specifications*

#### **CPU**

Intel® Pentium™ II / Celeron at 233 to 500MHz

#### **Cache**

L2 Cache is CPU Built-in

#### **Chipset**

PC100 BXcel

#### **BIOS**

1MB Flash EPROM (Supports PnP, APM, ACPI, ATAPI, DMI & Windows® 95)

IDE AUTO LBA Mode Supports HDDs over 8.4GB

Anti-Virus Protection

#### **System Memory**

Up to 768MB

Three 168-pin DIMMs

Synchronous DRAM (SDRAM) & 3.3V Extended Data Out (EDO)

DIMM Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB

Support ECC using parity DRAM Modules

#### **Expansion Slot**

Two ISA Bus Slots (with one shared with PCI)

Three PCI Bus Slots (with one shared with ISA)

One Accelerated Graphics Port (AGP)

### **Onboard I/O**

Support Two PCI Enhanced IDEs PIO Mode3, Mode4 and Ultra DMA 33 HDDs  
Twin Headers for Four IDE Device including IDE HDDs and CD-ROMs  
Support Two FDDs  
One ECP/EPP Parallel Port, Two 16550 UART Serial Ports, Two USB Ports  
(Optional ATX Form Factor Card)  
PS/2 Mouse Port (Optional Adapter Cable), Keyboard Port, IrDA Port (Optional  
TX/RX Module)

### **Onboard Sound**

3D Sound Pro Chipset support HRTF Positional Audio  
DirectSound & Software Wavetable Synthesizer, Digital Audio Interface (SPDIF  
IN/OUT)  
Support SB16, WSS & Game

### **Plug and Play**

Plug and Play Specification 1.1  
Plug and Play for DOS®, Windows® 3.x, Windows® 95

### **Other Features**

PC97/98 Ready  
Support SMM, APM and ACPI  
Comply to Energy Star "Green PC" Program  
Supports WAKE-ON-LAN (WOL)  
Supports Modem Ring-in Wake Up  
Trend Micro's Chip Away Virus and PC-Cillin included

All brand names and registered trademarks mentioned are property of their owners

---