

Model: AM-761BX

Intel® 82440BX Micro ATX Motherboard

Technical Specifications

CPU

Intel[®] Pentium[™] II / Celeron at 233 to 500MHz

Cache

L2 Cache is CPU Built-in

Chipset

Intel® 82440BX

BIOS

1MB Flash EPROM (Supports PnP, APM, ACPI, ATAPI, DMI & Windows® 95) IDE AUTO LBA Mode Supports HDDs over 8.4GB Anti-Virus Protection

System Memory

Up to 768MB Three 168-pin DIMMs Synchronous DRAM (SDRAM) & 3.3V Extended Data Out (EDO) DIMM Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB Supports ECC using parity DRAM Modules

Expansion Slots

One ISA Bus Slot (shared with a PCI slot) Three PCI Bus Slot (one shared with a ISA slot) One Accelerated Graphics Port (AGP)

Onboard I/O

Supports Two PCI Enhanced IDEs PIO Mode3, Mode4 and Ultra DMA 33 HDDs Twin Headers for Four IDE Device including IDE HDDs and CD-ROMs Supports Two FDDs One ECP/EPP Parallel Port, Two 16550 UART Serial Ports, Two USB Ports PS/2 Mouse Port, PS/2 Keyboard Port, IrDA Port (Optional)

Onboard Sound

3D Sound Pro Chipset supports HRTF Positional Audio DirectSound & Software Wavetable Synthesizer, Digital Audio Interface (SPDIF IN/OUT) Supports SB16, WSS & Game

Plug and Play

Plug and Play Specification 1.1 Plug and Play for DOS®, Windows® 3.x and Windows® 95

Other Features

PC97/98 Ready Supports SMM, APM and ACPI Comply to Energy Star "Green PC" Program Supports WAKE-ON-LAN (WOL) Supports Modem Ring-in Wake Up Trend Micro's Chip Away Virus and PC-Cillin included

All brand names and registered trademarks mentioned are property of their owners