

Model: AM-616



# VIA® Apollo Pro Chipset Micro ATX Motherboard





BIOS\_Upgrade\_(8/99)

# Technical Specifications

#### **Processor**

- Intel® Pentium II/III & Celeron.

- 233/266/300/333/350/400/450/500MHz or above. (66/100MHz Front Side Bus).

### Chip Set

- VIA® APOLLO Pro.

#### **BIOS**

- 2M Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI).

- IDE AUTO LBA Mode Supports HDDs over 8.4GB.

- Anti-Virus Protection.

#### **External Cache**

- L2 Cache is CPU Built-in.

### **Memory**

- Up to 768MB.

- Three 168-pins DIMMs (64bit).

- DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB.

#### On Board I/O

- Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33 HDDs. Twin Headers for Four IDE Devices Including IDE HDDs and CD ROMs.

- Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or

2.88MB.

- One ECP/EPP Parallel Port.

- Two 16550A UART Serial Ports.

- Two USB Ports.

- PS/2 Mouse Port.

- PS/2 Keyboard Port.

On Board Sound (Optional)

- Creative VIBRA 16XV.
- PnP, Creative 3D Enhancement, Wave Synth Wave Table.
  - Full-Duplex, Sound Blaster 16 Compatible.
  - Line-in, Line-out, Mic-in and MIDI/Game Port.

# **Hardware Monitoring (Optional)**

- Voltage, Temperature, Fan Speed Monitoring, CPU Over Heat Protection.

### **Expansion Slots**

- One ISA Bus Slots (One PCI Shared Slot).
- Three PCI Bus Slots (One ISA Shared Slot).
  - One Accelerated Graphics Port (AGP).

## **Plug and Play**

- Plug and Play Specification 1.1.
- Plug and Play for DOS®, Windows® 3.x, and Windows® 95.

# PC97/98

- PC97/98 Ready.

## **Power Management**

- Support SMM & APM.
- Comply to Energy Star "Green PC" Program.
  - Support WAKE-ON-LAN (WOL).
  - Support Modem Ring-in Wake Up.

# **PCI**

- PCI 2.1 Compliant.

# **AGP**

- AGP V1.0

# **VRM**

- On Board VRM 8.2.

### **Battery**

- On-board Lithium Battery.

### **Board Size**

- 175mm x 244mm, Micro ATX Form Factor.

All brand names and registered trademarks mentioned are property of their owners