Model: **AM-908**

VIA® Apollo Pro133 Chipset ATX Motherboard

BIOS_Upgrade_

Technical Specifications

Processor
- Intel® Pentium® III / Celeron™ (66/100/133Mhz Front Side Bus) .
- 500/533/550/600/650/667/700MHz or above for Pentium® III.
- 300/333/366/400/433/466/500/533MHz for Celeron™.

Chip Set
- VIA® Apollo PRO133 (596A or 596B + 693A).

BIOS
- 2M Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI).
- IDE AUTO LBA Mode Supports HDDs over 8.4GB.
- Anti-Virus Protection.
- Trend Micro ChipAway Virus Protection.

Cache
- L2 Cache is CPU Built-in.

Memory
- Size up to 768MB.
- Three 168-pins DIMMs.
- DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB.

On Board I/O
- Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33 Channels (Optional Ultra DMA 66 & Ultra DMA 66 Cable).
- Twin Headers for Four IDE Devices Including IDE HDDs and CDROMs.
- Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.
- One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Two USB Ports, PS/2 Mouse Port, PS/2 Keyboard Port.

On Board Sound (Optional)
- Creative ES1373 PCI Sound Chip.

- PnP, Creative 3D Enhancement, Wave Synth Wave Table.
- Full-Duplex, Sound Blaster 16 Compatible.
- Line-in, Line-out, Mic-in and MIDI/Game Port.

Expansion Slots
- Two ISA Bus Slots (One PCI Shared Slot).
- Five PCI Bus Slots.
- One Accelerated Graphics Port (AGP).

Plug and Play
- Plug and Play Specification 1.1.
- Plug and Play for DOS®, Windows® 3.x, and Windows® 95.

PC97/98
- PC97/98 Ready, PC99 Color Connector.

Power Management
- Support SMM, APM and ACPI.
- Comply to Energy Star "Green PC" Program.
- Supports WAKE-ON-LAN (WOL).
- Supports Modem Ring-in Wake Up.

PCI
- PCI 2.1 Compliant.

AGP
- AGP V1.0

VRM
- On Board VRM 8.4.

Battery
- On-board Lithium Battery.

Others
- CPU Frequency Multiplier Jumperless (Optional).
- Alarm Wake-up
- Bundle "PC-cillin 6" Anti Virus Software.

Board Size
- 173mm x 305mm, ATX Form Factor.