



## P4Twins-HDTV

- Socket 478 for Pentium® 4 / Celeron® D processor
- ATI™ Radeon Xpress 200
- ULi® 1573 Chipset
- Free Bundle VGA\_HDTV panel with VGA and 3 RCA-type component video output, that allows PC to connect to all high-definition component video input capability
- Chipset capable to FSB 1066 MHz, supports H-T Technology
- Supports DDR2 667 and DDR400 (DDR2 and DDR are supported separately)
- DirectX 9.0 on board VGA, Pixel Shader 2.0, Max. shared memory 128MB
- Integrated ATI™ X300-based 2D/3D graphics
- Hybrid Booster - Safe Overclocking Technology
- PCI Express x16 slot
- PCI Express x1 slot
- 4 ports of SATA 1.5Gb/s, support RAID 0, 1, JBOD, 2 ATA133 ports
- 7.1 Channel Superior Quality Audio, 10/100 Ethernet LAN
- ASRock 8CH I/O: 4 ready-to-use USB Ports, 7.1 channel audio

This model may not be sold worldwide. Please contact your local dealer for availability of this model in your region.

Specification

Support

Download

BIOS

Manual

FAQ

CPU Support List

## CPU Support List

Socket	Family	Number	Core	Frequency	FSB	Cache	Validated E
478	Pentium 4	n/a	Northwood	3.40 GHz	800MHz	512KB	All
478	Pentium 4	n/a	Prescott	3.40 GHz	800MHz	1MB	All
478	Pentium 4	n/a	Northwood	3.20 GHz	800MHz	512KB	All
478	Pentium 4	n/a	Prescott	3.20 GHz	800MHz	1MB	All
478	Pentium 4	n/a	Northwood	3.06 GHz	533MHz	512KB	All
478	Pentium 4	n/a	Northwood	3.00 GHz	800MHz	512KB	All
478	Pentium 4	n/a	Prescott	3.00 GHz	800MHz	1MB	All
478	Pentium 4	n/a	Northwood	2.80 GHz	800MHz	512KB	All
478	Pentium 4	n/a	Prescott	2.80 GHz	800MHz	1MB	All
478	Pentium 4	n/a	Northwood	2.80 GHz	533MHz	512KB	All
478	Pentium 4	n/a	Prescott	2.80 GHz	533MHz	1MB	All
478	Pentium 4	n/a	Northwood	2.66 GHz	533MHz	512KB	All
478	Pentium 4	n/a	Northwood	2.60 GHz	800MHz	512KB	All

Socket	Family	Number	Core	Frequency	FSB	Cache	Validated E
478	Pentium 4	n/a	Northwood	2.60 GHz	400MHz	512KB	All
478	Pentium 4	n/a	Northwood	2.53 GHz	533MHz	512KB	All
478	Pentium 4	n/a	Northwood	2.50 GHz	400MHz	512KB	All
478	Pentium 4	n/a	Northwood	2.40 GHz	800MHz	512KB	All
478	Pentium 4	n/a	Northwood	2.40 GHz	533MHz	512KB	All
478	Pentium 4	n/a	Prescott	2.40 GHz	533MHz	1MB	All
478	Pentium 4	n/a	Northwood	2.40 GHz	400MHz	512KB	All
478	Pentium 4	n/a	Northwood	2.26 GHz	533MHz	512KB	All
478	Pentium 4	n/a	Northwood	2.20 GHz	400MHz	512KB	All
478	Pentium 4	n/a	Northwood	2.00 GHz	400MHz	512KB	All
478	Pentium 4	G1	Prescott	3.40 GHz	800MHz	1MB	All
478	Celeron D	350	Prescott	3.20 GHz	533MHz	256KB	All
478	Celeron D	350(G1)	Prescott	3.20 GHz	533MHz	256KB	All
478	Celeron D	345	Prescott	3.06 GHz	533MHz	256KB	All
478	Celeron D	340	Prescott	2.93 GHz	533MHz	256KB	All
478	Celeron D	335	Prescott	2.80 GHz	533MHz	256KB	All
478	Celeron D	330	Prescott	2.66 GHz	533MHz	256KB	All
478	Celeron D	325	Prescott	2.53 GHz	533MHz	256KB	All
478	Celeron D	320	Prescott	2.40 GHz	533MHz	256KB	All
478	Celeron D	315	Prescott	2.26 GHz	533MHz	256KB	All
478	Celeron D	310	Prescott	2.13 GHz	533MHz	256KB	All
478	Celeron	n/a	Northwood	2.80 GHz	400MHz	128KB	All
478	Celeron	n/a	Northwood	2.70 GHz	400MHz	128KB	All
478	Celeron	n/a	Northwood	2.60 GHz	400MHz	128KB	All
478	Celeron	n/a	Northwood	2.50 GHz	400MHz	128KB	All
478	Celeron	n/a	Northwood	2.40 GHz	400MHz	128KB	All
478	Celeron	n/a	Northwood	2.30 GHz	400MHz	128KB	All
478	Celeron	n/a	Northwood	2.20 GHz	400MHz	128KB	All
478	Celeron	n/a	Northwood	2.10 GHz	400MHz	128KB	All
478	Celeron	n/a	Northwood	2.00 GHz	400MHz	128KB	All

If you need to update BIOS, please click [here](#).

The specification is subject to change without notice in advance. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

The above user interface picture is a sample for reference. The actual user interface may vary with the updated software version.



