

FKT333A Socket A Motherboa

<p>Picture N/A</p>	<p>Key Features</p> <ul style="list-style-type: none"> • ATX form factor • Support Socket A for AMD Athlon/Athlon XP/Duron • Support 3 DDR200/DDR266/DDR333 DIMMs • Support 1 4X AGP slot • Support 6 PCI Bus Master Slot • Support ATA-133 Hard Driver • Support 4 USB 1.1 Ports • Support AC-97 Audio • VIA LAN option (for VIA8233:ATA-100 only)
<p>CPU</p> <ul style="list-style-type: none"> - Support Socket A (Socket 462) for AMD® Athlon™ / Athlon XP / Duron™ processor. - Support 600MHz up to 2000+ MHz processor and higher. 	
<p>Chipset</p> <p>VIA® KT333 (552 BGA) Chipset</p> <ul style="list-style-type: none"> - FSB @200/266MHz - AGP 4X and PCI Advanced high performance memory controller <p>VIA® VT8233(A) (376 BGA) Chipset</p> <ul style="list-style-type: none"> - High Bandwidth V-link Client controller - Integrated Faster Ethernet LPC - Integrated Hardware Sound Blaster/Direct Sound AC97 audio. - Ultra DMA 66/100/133 master mode PCI EIDE controller - ACPI 	
<p>FSB</p> <ul style="list-style-type: none"> - 100/133 (200/266)MHz clocks 	
<p>Main Memory</p> <ul style="list-style-type: none"> - Support six memory banks using three 184-pin DDR DIMMs. - Support a maximum memory size up to 3GB. - Support 2.5v DDR200/266/333 DDR SDRAM DIMM. 	
<p>Slots</p> <ul style="list-style-type: none"> - One AGP (Accelerated Graphics Port) slot. * AGP 2.0 4X specification compliant. - Six 32-bit Master PCI Bus slots. - Supports 3.3V/5V PCI bus Interface. 	
<p>On-Board IDE</p> <ul style="list-style-type: none"> - An IDE controller on the VIA® VT8233(A) chipset provides IDE HDD/CD-ROM with PIO, Bus Master and Ultra DMA 66/100/133 operation modes - Can connect up to 4 IDE devices 	
<p>Audio</p> <p>Integrated AC-97 audio Chipset</p> <ul style="list-style-type: none"> - Direct Sound AC'97 Audio 	
<p>On-Board Peripherals</p> <p>On-Board Peripherals include:</p> <ul style="list-style-type: none"> - 1 floppy port supports 2 FDD with 360K, 720K, 1.2M, 1.44M and 2.88Mbytes - 2 serial ports (COMA and COMB) - 1 parallel port supporting SPP/EPP/ECP mode - 1 IrDA connector for SIR/ASKIR/HPSIR - 1 Audio/Game port - 4 USB 1.1 ports (2 on board, 2 extend) 	
<p>BIOS</p> <ul style="list-style-type: none"> - The mainboard BIOS provides "Plug & Play" BIOS which detects the peripheral devices and expansion cards of the board automatically. 	
<p>Dimension</p> <p>30.4 cm(L) x 24.5 cm(W) ATX Form Factor.</p>	

[About Firstech](#)

[Product](#)

[e-Service](#)

[NEWS](#)

[Conte](#)