

Motherboard

[Motherboard](#)

[Video Card](#)

[Network Card](#)

[Sound Card](#)

GC-8601MT



Download :

[Bios](#)

[Driver](#)

[Manual](#)

Specification:

Designed for Pentium III, Tualatin & Celeron Processor by using VIA Chipset

- Support Intel Pentium III, Tualatin, FCPGA, Celeron PPGA or Cyrix III Processor on Socket 370
- VIA VT8601T PLE133 Chipset, Support 66/100/133MHz Processor Front-side Bus
- AGP Graphics Controller Integrated inside VIA VT8601T chipset
- Dynamic Graphics Memory Allocation on System Memory up to 8MB
- High AGP Performance with up to 533MB/sec Transfer Rate
- rCADE3D Accelerator with 4Kbyte 3D Texture Cache
- Hardware MPEG-2 Architecture for DVD Video Playback with AC-3
- Extended Screen Resolution up to 1600x1200 with 24-bit True Color
- Full Support for Microsoft Direct 3D and Direct Draw
- VIA VT82C686B Super South Bridge
- Full Software Configurable: CPU PnP and full jumper less
- Modem Ring Wakeup with External Modem
- Interface Header to Support Wake-On-LAN Enabled Ethernet Card
- 3x 168-pins DIMMs, support up to 1.5GB Memory Capacity
- Support 133MHz SDRAM DIMM
- 1x AMR slot, 2x PCI slots
- 1x FDD port, 1x LPT port, 2x COM ports
- 4x USB ports, 1x PS/2 mouse port, 1x IrDA port
- Dual IDE channels supporting four Ultra ATA33/66/100 IDE devices
- System Health Monitoring with Win98/95/NT Support
- Award 2MB BIOS, PC99/ACPI/DMI Compliant
- MATX Format, 215mm x 190mm PCB
- Integrated AC97 Audio Onboard
- AC97 2.1 Compliant Codec with 3D Stereo Enhancement
- SoundBlaster Pro Hardware for DOS Mode Compatibility
- Complete Driver Support for Win95/98/2000/NT
- 1x Line-out, 1x Line-in, 1x Mic-in
- 1x CD-in, 1x AUX-in, 1x Telephony Port, 1x Game Port

E-mail: info@champion-first.com