



Welcome To
www.Hoxtek.Com

F651 Motherboard

Tournaments:

- Home Page
- About us
- FAQs

Download:

- BIOS
- Chipset driver
- VGA driver
- Audio driver
- IAA
- IDE driver
- LAN driver



[Click to see big image](#)

Key Features

- **Micro-ATX form factor**
- **Support Intel P4 processor with 533MHz system bus**
- **Support maximum 2GB DDR333 SDRAM with 2 DIMMs**
- **Support one 15 pins VGA port for integrated graphics**
- **Support one 1.5V AGP 2X/4X slot for AGP add on**
- **Support 3 PCI slots**
- **Support 6 USB 2.0 ports**
- **Realtek 8100B LAN on board option**

CPU

- Supports Intel® Pentium® 4 processors in the 478 pin package.
- Supports 1.5GHz, 1.6GHz, 1.7GHz, 1.8GHz, 1.9GHz, 2.2GHz and up.

Chipset

SIS® 651 Graphics Integrated DDR333 Chipset

- Supports DIMMs of DDR333/DDR266/DDR200 SDRAM memory.
- Supports 533MHz system bus with 2X address and 4X data rate.
- Supports AGP 4X/2X interface with fast write transaction.

SIS® 962 MuTIOL® Media I/O Chipset

- Bi-directional 16-bit data bus with 533MB bandwidth.
- 2-channel Ultra ATA 133/100/66/33 Bus Master IDE controller.
- Dual USB 2.0 controllers (expanded capabilities for 6 ports).
- Supports AC'97 V2.2 audio codec and modem codec.
- ACPI 1.0b and APM 1.2 compliant.
- LPC 1.0 interface.
- PCI 2.2 interface.

FSB

- Supports Intel P4 533MHz System Bus

Main Memory

- Support six memory banks using three 184-pin DDR DIMMs.
- Supports up to 2GB DDR333/DDR266/DDR200 with 2 DDR DIMMs
- Support 2.5v DDR SDRAM DIMM.

● Slots

- One AGP (Accelerated Graphics Port) 4X slot.
- Three PCI 2.2 32-bit PCI bus slots (support 3.3v/5v PCI bus interface).

● On-Board IDE

- An IDE controller on the SiS962 chipset provides IDE HDD/CD-ROM with PIO, Bus Master and Ultra DMA 133/100/66/33 operation modes.
- Can connect up to 4 IDE devices.

● Audio

- AC'97 Codec.

● On-Board Peripherals

- 1 VGA port for integrated graphics display
- 1 floppy port supports 2 FDDs with 360K, 720K, 1.2M, 1.44M and 2.88Mbytes.
- 1 serial ports (COM A) and 1 expansion serial port(COM B).
- 1 parallel port supports SPP/EPP/ECP mode.
- 4 USB 2.0 ports on board and 1 heads for extra 2 ports expansion.
- 1 IrDA connector for SIR.
- Audio port.
- 1 extend game port.
- 1 RJ45 LAN connector for LAN on board option

● BIOS

- The mainboard BIOS provides "Plug & Play" BIOS which detects the peripheral devices and expansion cards of the board automatically.

● Dimension

- 24.5 cm(L) x 24.5 cm(W) Micro-ATX Form Factor.

Copyrights © 2003 Hoxtek.com All rights reserved.

If you have any suggestions or ideas about this web site, don't hesitate to [E-Mail](#) them to me.
I will try to satisfy everybody's needs.