



Welcome To  
www.Hoxtek.Com

## FKT333A Socket A Motherboard

### Tournaments:

- Home Page
- About us
- FAQs

### Download:

- BIOS
- Chipset driver
- VGA driver
- Audio driver
- IAA
- IDE driver
- LAN driver

Picture NA

### Key Features

- **ATX form factor**
- **Support Socket A for AMD Athlon/Athlon XP/Duron**
- **Support 3 DDR200/DDR266/DDR333 DIMMs**
- **Support 1 4X AGP slot**
- **Support 6 PCI Bus Master Slot**
- **Support ATA-133 Hard Driver**
- **Support 4 USB 1.1 Ports**
- **Support AC-97 Audio**
- **VIA LAN option (for VIA8233:ATA-100 only)**

### CPU

- Support Socket A (Socket 462) for AMD<sup>®</sup>Athlon™/ Athlon XP / Duron™processor.
- Support 600MHz up to 2000+ MHz processor and higher.

### Chipset

VIA<sup>®</sup> KT333 (552 BGA) Chipset

- FSB @200/266MHz
- AGP 4X and PCI Advanced high performance memory controller

VIA<sup>®</sup> VT8233(A) (376 BGA) Chipset

- High Bandwidth V-link Client controller
- Integrated Faster Ethernet LPC
- Integrated Hardware Sound Blaster/Direct Sound AC97 audio.
- Ultra DMA 66/100/133 master mode PCI EIDE controller
- ACPI

### FSB

- 100/133 (200/266)MHz clocks are supported.

### Main Memory

- Support six memory banks using three 184-pin DDR DIMMs.
- Support a maximum memory size up to 3GB.
- Support 2.5v DDR200/266/333 DDR SDRAM DIMM.

### Slots

- One AGP (Accelerated Graphics Port) slot.  
\* AGP 2.0 4X specification compliant.
- Six 32-bit Master PCI Bus slots.
- Supports 3.3V/5V PCI bus Interface.

### On-Board IDE

- An IDE controller on the VIA<sup>®</sup> VT8232(A) chipset provides IDE HDD/CD-ROM with PIO, Bus Master and Ultra DMA 66/100/133 operation modes
- Can connect up to 4 IDE devices

### Audio

- Integrated AC-97 audio Chipset
- Direct Sound AC'97 Audio

### On-Board Peripherals

On-Board Peripherals include:

- 1 floppy port supports 2 FDD with 360K, 720K, 1.2M, 1.44M and 2.88Mbytes
- 2 serial ports (COMA and COMB)
- 1 parallel port supporting SPP/EPP/ECP mode
- 1 IrDA connector for SIR/ASKIR/HPSIR

- 1 Audio/Game port
- 4 USB 1.1 ports (2 on board, 2 extend)

**BIOS**

- The mainboard BIOS provides "Plug & Play" BIOS which detects the peripheral devices and expansion cards of the board automatically.

**Dimension**

30.4 cm(L) x 24.5 cm(W) ATX Form Factor.

Copyrights © 2003 Hoxtek.com All rights reserved.

If you have any suggestions or ideas about this web site, don't hesitate to [E-Mail](#) them to me.  
I will try to satisfy everybody's needs.