



Company Profile

## HS-486H

- Multi I/O
- WDT
- PC/104

5x86 Half Size ISA Bus SBC

Products



ISB

### ► SPECIFICATIONS

Backplane

Chassis

Power Supply

Peripheral

BareBone

Services & Supports

User's Manual

Drivers

Environmental Policy

News

- **CPU:** 486X/DX/DX2/DX4 or Cyrix/AMD 5x86 CPU
- **Bus Interface:** ISA Bus
- **Chipset:** UMC 8498/8496
- **Memory:** Two SIMM sockets provides up to 64MB
- **IDE Interface:** Provides up to two IDE disk drives
- **Floppy Interface:** Supports up to two floppy disk drives.
- **Parallel Port:** Supports SPP/ECP/EPP.
- **Serial Port:** Two RS-232 serial ports including NS16C550 UART
- **Watch-Dog Timer:** Set 1, 2, 10, 20, 110, or 220 seconds, activity trigger with Reset or NMI
- **DMA Channels:** 7
- **Interrupt Levels:** 15
- **Keyboard :** PS/2 6pin Mini Din
- **Mouse:** PS/2 6pin Mini Din.
- **DiskOnChip™:** Socket for DiskOnChip™.
- **CMOS:** DS12887 chip and quartz oscillator, 128B CMOS memory, powered by lithium battery for over 10 years of date retention
- **Extra Power:** One 8pin extra power connector
- **Power Voltage:** +5V@1.56A, 12V@20mA, -12V@20mA
- **Operating Temperature:** 0-55°C.
- **Board Size:** 7.3"(L) x 4.8" (W).

### ► ORDERING INFORMATION

- **Model:** HS-486H

---

[|Home|](#)[Company Profile|](#)[Services & Supports|](#)[Environmental Policy|](#)[News|](#)